


MWL series



HPL.1 series

SPECIFICATIONS:

- Round profile low voltage LED lighting fixture system with acrylic lens, stem mount.

Housing Channel:

- 1 3/8" O.D. extruded aluminum. Custom lengths available
- Aluminum endcap
- Choice of anodized or powdercoat painted finishes.
- Extruded clear acrylic with internal diffusing lens and snap-in fit.

Stems and Support Brackets:

- 1/8 I.P. x 3" O.A.L. standard.
- Powerfeed support stem with fixed position at end of fixture.
- Adjustable support brackets supplied for end and intermediate positioning. Intermediate support stems included; one support bracket up to 3' housing length, two from 3' to 6', and three from 7' to 8'.

Clikstrip (included)

- CLX type with 1-7/8" o.c. lamp spacing

LEDs (included)

- Choice of MWL and HPL.1 series LED module spaced 1-7/8" o.c. Specify series. Included
- MWL (12Vac or 24Vac); HPL.1 (24 vac only)
- Choice of 2800K, 3500K, and 5000K color temperatures.

Electrical:

- Magnetic AC transformer power supply. Ordered separately.

Compliances:

- UL/C listed as surface mounted luminaire only. Consult with NEC or local electrical inspector for other uses.
- Suitable for damp locations.

Ordering Information

To specify a complete catalog number, choose one item from the selection available in each module. (Clikstrip included)

A complete fixture consists of a housing, support stems, LEDs, and remote transformer. Transformer ordered separately.

Example: CRS-M352-02F-WH

CRS - - -

| | | | | | | |
|-----|----|----|---|-----|---|-----|
| CRS | -X | XX | X | -XX | X | -XX |
|-----|----|----|---|-----|---|-----|

Series

CRS Stem mount

Lamp type

CRS -M MWL series (standard output)
CRS -H HPL.1 series (high output)

Lamp style

CRS -X 28 2800K
CRS -X 35 3500K
CRS -X 50 5000K

Lamp voltage

CRS -X XX 2 12 volt AC
CRS -X XX 4 24 volt AC

Length (consult factory for custom lengths available in 1/8" increments from 1' to 8')

CRS -X XX X -01-08 1' - 8' in 1' increments

CRS -X XX X -05-25 0.5 - 2.5 meters in half meter increments

Unit of measure

CRS -X XX X -XX F Feet

CRS -X XX X -XX M Meters

Finish

CRS -X XX X -XX X -WH White paint

CRS -X XX X -XX X -BK Black paint

CRS -X XX X -XX X -MS Metallic silver paint

CRS -X XX X -XX X -BZ Bronze paint

CRS -X XX X -XX X -SA Satin aluminum anodized

CRS -X XX X -XX X -SG Satin gold anodized

222364
08-29-08