



MiT5

MiT5





type:

LINEAR T5 FLUORESCENT

low profile T5 fluorescent fixture

- SPECIFICATIONS**
- Fully assembled housing is formed and welded, 20 ga. steel, chemically treated to resist corrosion and enhance paint adhesion
 - Standard finish is high reflectance white powder coat, applied post production
 - Knock-outs accept standard electrical fittings (by others)
 - Rotational locking lamp holders
 - Available for one or two T5 14W, 21W, 28W, 35W and high output 24W, 39W, 54W, 80W linear fluorescent lamps
 - Standard 120V or 277V, 50-60Hz electronic high power factor ballast is pre-wired to the lamp holders
 - Dimming and emergency battery back up options available (**consult factory for availability and system compatibility**)
 - UL and ULC listed for dry and damp locations
 - IBEW
 - Made in the U.S.A.

NOTE: Includes program rapid start ballast.



SPECIFICATION / ORDER FORMAT						DIMENSIONAL INFO.
model no.	lamp position	wattage - lamp	voltage	wiring method	options	overall length
MiT5	-1T	14 - 14w T5	/UNV-120-277V	/RS	Dimming - (consult factory)	22-1/2"
	-1S	21 - 21w T5	/347		/EB - emergency ballast	34-5/16"
	-2S	28 - 28w T5			(consult factory)	46-1/16"
	-RA	35 - 35w T5			/DL - damp location	57-15/16"
		24 - 24w T5 HO			/CU - custom finish	22-1/2"
		39 - 39w T5 HO			(consult factory)	34-5/16"
		54 - 54w T5 HO				46-1/16"
		80 - 80w T5 HO				57-15/16"

LENSES | Two-piece system comprised of polycarbonate channel and striated snap-on cover


M5LNP	Clear fine prismatic acrylic lens with mounting clips (sold by the foot)	___ft.
M5LNCF	Frosted acrylic lens with mounting clips (sold by the foot)	___ft.

TUBE GUARD |

TG	Tube Guard (sold by the foot)	___ft.
----	-------------------------------	--------

CABLE KIT |

BAC-4N-W	Aircraft suspension kit, 4', white
BAC-4P-W	Aircraft suspension kit w/ power feed, 4', white

REFLECTORS | 20 ga. steel construction, white powder coat finish (consult factory for optional reflector materials and finishes)


R1

SYMMETRICAL

MiT5-1T-R1-14/24
 MiT5-1T-R1-21/39
 MiT5-1T-R1-28/54
 MiT5-1T-R1-35/80

for fixture models

MiT5-1T14 MiT5-1T24
 MiT5-1T21 MiT5-1T39
 MiT5-1T28 MiT5-1T54
 MiT5-1T35 MiT5-1T80




R2

ASYMMETRICAL

MiT5-1T-R2-14/24
 MiT5-1T-R2-21/39
 MiT5-1T-R2-28/54
 MiT5-1T-R2-35/80

MiT5-1T14 MiT5-1T24
 MiT5-1T21 MiT5-1T39
 MiT5-1T28 MiT5-1T54
 MiT5-1T35 MiT5-1T80



R3

INSIDE ASYMMETRICAL

MiT5-1T-R3-14/24
 MiT5-1T-R3-21/39
 MiT5-1T-R3-28/54
 MiT5-1T-R3-35/80

MiT5-1T14 MiT5-1T24
 MiT5-1T21 MiT5-1T39
 MiT5-1T28 MiT5-1T54
 MiT5-1T35 MiT5-1T80




RE

ELLIPTICAL

MiT5-1T-RE-14/24
 MiT5-1T-RE-21/39
 MiT5-1T-RE-28/54
 MiT5-1T-RE-35/80


MiT5-1T14 MiT5-1T24
 MiT5-1T21 MiT5-1T39
 MiT5-1T28 MiT5-1T54
 MiT5-1T35 MiT5-1T80



R4

MiT5-1S-R4-14/24
 MiT5-1S-R4-21/39
 MiT5-1S-R4-28/54
 MiT5-1S-R4-35/80

MiT5-1S14 MiT5-1S24
 MiT5-1S21 MiT5-1S39
 MiT5-1S28 MiT5-1S54
 MiT5-1S35 MiT5-1S80



R5

MiT5-2S-R5-14/24
 MiT5-2S-R5-21/39
 MiT5-2S-R5-28/54
 MiT5-2S-R5-35/80

MiT5-2S14 MiT5-2S24
 MiT5-2S21 MiT5-2S39
 MiT5-2S28 MiT5-2S54
 MiT5-2S35 MiT5-2S80

MiT5-RA-R4-14/24
 MiT5-RA-R4-21/39
 MiT5-RA-R4-28/54
 MiT5-RA-R4-35/80

MiT5-RA14 MiT5-RA24
 MiT5-RA21 MiT5-RA39
 MiT5-RA28 MiT5-RA54
 MiT5-RA35 MiT5-RA80