

Recessed wall luminaires with directed light

Housing: Constructed of die-cast and extruded aluminum components with integral wiring compartment. Mounting tabs provided.


Enclosure: One piece die-cast aluminum faceplate. Clear tempered glass; .125" thick, machined flush to faceplate surface. Faceplate is secured by four (4) flush, socket head, stainless steel captive screws threaded into stainless steel inserts in the housing casting. Pure anodized aluminum asymmetrical reflector. Continuous high temperature, molded silicone rubber gasket for weather tight operation.

Electrical: Compact fluorescent lampholder: 2G11, 4-pin, rated 75 W, 600 V. Ballast: Electronic, HPF for -18 °C starting, universal voltage (120 V through 277 V). Through Wiring: Maximum four (4) No. 12 AWG conductors (plus ground) suitable for 75 °C. Provided with two (2) 1/2" NPT threaded conduit entries.

Finish: Available in four standard BEGA colors: Black (BLK); White (WHT); Bronze (BRZ); Silver (SLV). To specify, add appropriate suffix to catalog number. Custom colors supplied on special order.

UL listed, suitable for wet locations and for installation within 3 feet of ground. Type non-IC. Protection class: IP65.

Type:
 BEGA Product:
 Project:
 Voltage:
 Color:
 Options:
 Modified:



	Lamp	Lumen	A	B	C
2224 P ADA	1 18W CF twin-4p*	1200	13	4 7/8	4

* Use only 9.0" MOL lamps

