

Surface-mounted ceiling downlights for fluorescent lamps

Housing: Two piece die-cast aluminum provided with a universal mounting bracket for direct attachment to a 4" octagonal wiring box. Die castings are marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy.

Enclosure: Tempered clear glass, retained by a one piece, die-cast aluminum step baffle frame. Frame is secured by one stainless steel captive screw threaded into a stainless steel insert. Internal reflector made from pure, anodized aluminum. Fully gasketed for weather tight operation using molded silicone rubber "U-channel" gasket.

Electrical: Fluorescent lampholders are type GX24q-1 (13W). Ballast is 120V only.

Finish: All BEGA standard finishes are polyester powder coat with minimum 3 mil thickness. Available in four standard BEGA colors: Black (BLK); White (WHT); Bronze (BRZ); Silver (SLV). To specify, add appropriate suffix to catalog number. Custom colors supplied on special order.

UL listed for US and Canadian Standards, suitable for wet locations. Protection class IP65.

Type:
BEGA Product:
Project:
Voltage:
Color:
Options:
Modified:



				Lumen	β	A	B
5611 P	1	13W	CF triple-4p	900	87°	5	7 7/8

β = Beam angle

