

# Trims for 3" Low Voltage Recessed Housings

Catalog No.\_\_\_\_\_

Proiect \_\_\_\_

Type \_

## Specifications/Features

## All trims have white trim finish unless specified.

Maximum lamp rating for most trim options: 20-50W 12V MR-16 lamp, GU5.3 base.

All trims are cULus listed and suitable for damp locations; only shower trims are listed for wet locations.

On recessed trims designed for use with MR16 lamps, Con-Tech Lighting provides a clear, tempered safety glass. This safety glass should only be used with open MR16 lamps, and not used with MR16 lamps that contain an integral glass lens. If use of MR16 with front glass is required, remove the factory provided clear tempered safety lens.

\*See back for descriptions of Reflector/Trim Finish options.



### CTR301-B

Adjustable Black Baffle, Black Trim CTR301-P

#### Adjustable Black Baffle

#### CTR301-WHT

Adjustable White Baffle

15° Vertical swing, 45mm lens. Trim can hold up to two (2) lenses with stepped lens holder (included). Insert 45mm lens on lower level of lamp seat, instert 50mm lens onto higher level.



### CTR302-B-BLK

Adjustable Multiplier; Black Metal Trim Ring, Black Reflector

## CTR302-P-(CLR, BLK, WHT)

Adjustable Multiplier; White Metal Trim Ring, Select Reflector Finish

#### CTR302-(ST, NK)-CLR

Adjustable Multiplier; Select Metal Trim Finish, Clear Reflector

37° Vertical adjustment, 45mm lens. Trim can hold up to two (2) lenses with stepped lens holder (included). Insert 45mm lens on lower level of lamp seat, instert 50mm lens onto higher level.



**Oblong Slot** 

## CTR303N-B

Slotted Wall Wash; Black Trim CTR303N-P

#### Slotted Wall Wash; White Trim

Internal 50° swing adjustment, external 358° rotation. Slot aperture permits maximum beam area adjustment for either wall wash or concealed accent lighting effects. Black interior surface, 45mm Lens.



#### CTR304-B-BL Angled Wall Wash; Black Reflector CTR304-P-CLR

Angled Wall Wash; Chrome Reflector

### CTR304-S-PL

Angled Wall Wash; Platinum Reflector, Silver Trim Adjustable lampholder with 55-75° aiming angle. 45mm Lens. Trim can hold up to two (2) lenses with stepped lens holder (included). Insert 45mm lens on lower level of lamp seat, instert 50mm lens onto higher level.



1-3/8" Aperture

Pin Spot; Black Cut-Off Reflector, Black Trim Ring CTR305-BLK

Pin Spot; Black Cut-Off Reflector

#### CTR305-CLR

CTR305-B-BLK

Pin Spot: Clear Cut-Off Reflector

Downlight Only, 50mm Lens. Trim can hold up to two (2) lenses with stepped lens holder (included). Insert 45mm lens on lower level of lamp seat, instert 50mm lens onto higher level.



### CTR306-P

Surface Adjustable; Black Baffle

40° Vertical adjustment, 359° horizontal rotation. 50mm Lens. Regressed black baffle reduces surface brightness. Flat, stainless mounting clips hold trim firmly to ceiling. Trim can hold up to two (2) lenses with stepped lens holder (included). Insert 45mm lens on lower level of lamp seat, instert 50mm lens onto higher level.



### CTR307-(P, B, NK)

Adjustable Pin Spot; Black Baffle, Select Trim Finish

## **CTR307-WHT**

Adjustable Pin Spot; White Baffle, White Trim Deep baffle for maximum lamp concealment. May be used as a pin spot style downlight or an adjustable accent light. 35° Vertical adjustment. 45mm Lens. Trim can hold up to two (2) lenses with stepped lens holder (included). Insert 45mm lens on lower level of lamp seat, instert 50mm lens onto higher level.



#### CTR310-F-P Fluted Frosted Glass Diffuser

Must use Front Glass MR16 Lamp. 1-1/4" Drop from ceiling. Cylindrical shape focuses light downward, eliminates glare.



### CTR311FR-(NK, P)

Frosted Flat Glass; Select Trim Finish Shower light trim, double neoprene gasketed. cULus Listed for wet location.



CTR312-P Flat Glass; White Trim Etched Glass for light diffusion.

Continued on page 2



Catalog No.	





ONIECH IGHTING

#### CTR313-P

Convex Drop Lens; Select Trim Finish Shower light trim. 3/4" Drop (ceiling to bottom of glass), double neoprene gasketed. cULus listed for wet location.



### CTR321-F-(NK, P)

Frosted Glass Cylinder; Select Trim finish Cylindrical glass diffuser, specular reflector. Light is focused downward, glare is eliminated. Cast aluminum trim construction. 1-1/4" Drop from ceiling.



#### CTR335-(B, CO, NK, P) Elbow; Select Finish

Exceptional aiming flexibility with 87° vertical, 359° rotation adjustment. Die-casst aluminum construction. Front access, spring latch lamp retainer ring, black finish (optional white retainer rign available: **1623/224** WHITE, ordered

separately). Maximum depth from ceiling: 2-1/2". 47mm lens. Accepts only one 47mm lens; if louver is required (**FA-16 45MM**), remove safety lens and use front glass MR16 lamp.



### CTR305SQ-SQ-B-CLR

Square Pin Spot, Black Trim, Clear Reflector CTR305SQ-SQ-P-CLR

Square Pin Spot, White Trim, Clear Reflector CTR305SQ-SQ-NK-CLR

Square Pin Spot, Brushed Nickel Trim, Clear Reflector

Downlight Only, 50mm Lens.



#### CTR317-P

Trims for 3"

Floating Ring; White Trim

Low Voltage Recessed Housings

Decorative floating glass ring, 2" center opening. Clear reflector with diffuse plastic cone. 1-1/8" Drop from ceiling. Cast aluminum trim construction. 50mm Lens.



CTR324- (P, NK, ST ) Fully Adjustable; Select Finish

Unsurpassed aiming flexibility: 87° vertical, 359° rotational. Front access, spring latch lamp retainer ring, black finish (optional white retainer rign available: **1623/224 WHITE,** ordered separately). Exclusive stainless flat springs insure firm, close-to-ceiling mounting. Accepts only one 47mm lens; if louver is required (**FA-16 45MM**), remove safety lens and use front glass MR16 lamp.



## CTR301SQ-B

Adjustable Black Baffle, Black Trim

## CTR301SQ-P

Adjustable Black Baffle, White Trim

#### CTR301SQ-WHT

Adjustable White Baffle, White Trim

Deep baffle traps stray light and conceals the lamp. May be used as a downlight or adjustable accent light 15° Vertical swing, 45mm lens. Trim can hold up to two (2) lenses with stepped lens holder (included). Insert 45mm lens on lower level of lamp seat, insert 50mm lens onto higher level.



#### CTR306SQ-B Surface Adjustable Bla

Surface Adjustable Black Trim; Black Baffle CTR306SQ-P

Surface Adjustable White Trim; Black Baffle 40° Vertical adjustment, 359° horizontal rotation. 50mm Lens. Regressed black baffle reduces surface brightness. Flat, stainless mounting clips hold trim firmly to ceiling.



## CTR318-F

Project \_

White Frosted Glass Cone

**Must use Front Glass MR16 Lamp.** Tapered glass diffuser, specular reflector. 1-1/4" Drop from ceiling. 50mm Lens.



## CTR325- (P, B, NK)

Fully Adjustable; Select Finish

Die cast, fully adjustable, round lampholder and backplate. Easy relamping with twist-off front retaining ring. Unsurpassed aiming flexibility: 87° vertical, 359° rotational. 50mm lens.



## CTR302SQ-B-(BLK, CLR)

Adjustable Multiplier; Black Trim, Black or Clear Reflector

#### CTR302SQ-P-(CLR, WHT)

Adjustable Multiplier; White Trim, Clear or White Reflector

Multipliers utilize a highly polished, specular reflector to maximize light intensity while concealing the light source. May be used as a downlight or adjustable accent light.

37° Vertical adjustment, 45mm lens. Trim can hold up to two (2) lenses with stepped lens holder (included). Insert 45mm lens on lower level of lamp seat, instert 50mm lens onto higher level.

### **Reflector/Trim Finish Legend**

All finishes are not available for all trims.

#### **Reflector Finish Options:**

BLK - Black Specular PL - Matte Platinum	CLR - Clear Specular WHT - White Specular
Trim Finish Options:	
B - Black	NK - Nickel
BC - Black Chrome	P - White
C - Chrome	S - Silver
CO- Brushed Copper	ST - Brushed Stainless
	Steel