

DESCRIPTION

The Corelite Z3 recessed luminaire meets the demands of the new energy culture with superior lighting and energy performance. Its engineered optical system delivers luminaire efficiencies greater than 85% while maintaining a soft luminous glow for high visual comfort. Its unique light distribution fills the volume of space to ensure that vertical surfaces glow to create the perception of spaciousness. To further realize the design potential of the Z3 series, it is available with a complete palette of shielding options, and lamp options, including T5, T8, LED and compact fluorescent, and maintains the series dedication to shallow plenum applications with a minimal 3-3/4 inch deep housing.

SPECIFICATION FEATURES

A ... Construction

Low profile housing constructed of die-formed 20 gauge cold rolled steel with integral 20 gauge gear tray.

B ... Reflectors

Precision tooled, high reflectance sheet metal, which allows for easy access to ballast compartment.

C ... Shielding

Extruded acrylic center optic with frosted acrylic side lenses. Lenses secured to housing via injection molded inserts for easy lamp access.

D ... Electrical

CFL fixtures use UL listed Class P, CFL program rapid start and instant start universal voltage electronic ballasts, power factors on lamp wattage and supply voltage, with less than 10% THD. Fixtures and electrical components certified to UL and CUL standards.

E ... Finish



Fixture housings are high reflectance white using electrostatically applied polyester powder coat paint.

Mounting

Standard flange design works with most lay-in ceiling types. Integral pryout tabs secure luminaire to ceiling grid from above. Fixture offers tie-in locations for tie-wire on all corners, consult local code for appropriate tie-wire recommendations.

NOTE: Concealed Ceiling

Class R may be installed into inaccessible ceilings (sheet rock, wood panel, etc.). This is achieved with the Metalux DFW series drywall frame-in kit, ordered separately from Metalux. Specify "CC" for the Corelite Ceiling Type. Specify the following part numbers separately, from Metalux: For 2x2, order Metalux part # DF-22W-U



CLASS Z3

Linear Prismatic Lens

2 LAMP CFL
(40W / 50W / 55W)

2'x2' Recessed
3-3/4" Depth



ORDERING INFORMATION

Sample Number: Z3-WL-240-1C-UNV-22-T1

Series	Shielding	Lamp Type	Wiring ¹	Voltage ¹	Ceiling Type	Options ¹
Z3: Class Z3	L: Linear Prismatic Lens	40: 40W CFL 50: 50W CFL 55: 55W CFL	B: Battery Pack C: Standard Circuit D: Dimming / Step Dimming E: Emergency T: Nightlight Y: Daylight	120: 120V 277: 277V 347: 347V UNV: Universal (120V-277V)	T1: 1" Grid, Slot-Grid, 9/16" Tegular T9: 9/16" Grid CC: Concealed Ceiling SU: Surface Mount	AR: Air Return CP: Chicago Plenum SD: Step Dimming W6: 6' Whip Flex W12: 12' Whip Flex
Reflector W: White	Number of Lamps 2: 2 Lamps	Number of Circuits 1: 1 Circuit 2: 2 Circuits		Size 22: 2' x 2'		

Notes: 1 Not all options available. Please consult your Cooper Lighting Representative for availability. Specifications and dimensions subject to change without notice.