

Features


- Low-profile reflector and lamp covers provide a sleek, modern appearance.
- Shallow housing requires only 3-5/8" of plenum space, great for applications with shallow plenums.
- Provides soft, uniform lighting without hot spots or dark areas.
- Direct lighting component is provided by a one-piece perforated metal cover with a white acrylic overlay or two-piece frosted glass diffuser that minimizes lamp images.
- Indirect lighting component provided by a reflector painted matte white for soft uniform visual appearance.
- **Housing edge design locates the bottom of the luminaire flush with the ceiling plane in standard (NEMA G) grid or screw slot (NEMA SS) applications.**
- **NOT suitable for use in narrow face grid (NEMA NFG) applications.**
- Glass diffuser option replaces the perforated basket with two frosted, ridged glass panels and natural satin finished metal hinge panels to introduce premium finishes and textures.
- UL listed for damp locations. Units incorporating emergency ballasts UL listed for dry locations.
- Suitable for row mounting.
- Lamp cover swings down for easy lamp and ballast access.
- **Hold down clips available, cat. # AVHD (sold separately.)**

Product Availability

Size	Shielding	Number of Lamps	Lamp Type	Ceiling Availability	Height in. (mm)
2'x2'	PMW	2	14, 24HO, CF40, CF50, CF55	G/T**	3-5/8"*** (92)
2'x2'	FGL	2	14, CF40	G/T**	3-5/8"*** (92)
2'x4'	PMW	2,3	28, 54HO	G/T**	3-5/8" (92)
2'x4'	FGL	2	28	G/T**	3-5/8" (92)

**Standard models are suitable for use in standard grid or screw slot ceilings, NOT suitable for use in narrow faced grid.

Dimensions



***2x2 models with emergency ballast or multiple ballasts are 5-1/4".

Architectural Fluorescent

Arioso® Essence

Recessed Architectural



Arioso Essence is a recessed direct/indirect luminaire with a sleek, shallow appearance and perforated metal or frosted glass lamp cover options.

Accessories

- AVHD** – Hold down clips
- FMA22** – 2'x2' "F" mounting frame for NEMA "F" mounting.
- FMA24** – 2'x4' "F" mounting frame for NEMA "F" mounting.

See page 190 for details on the "F" mounting frame.

Green Product Choice: 2AVEG228-PMW-UNV-1/2-EB95-LPT835HL*

2	AVE	G	-	-	-	
Width 2 - 2'	Family AVE – Arioso Essence	No. of Lamps (not included) 2 3	Shielding PMW – Perforated metal with white overlay FGL – Two-piece frosted ridged glass	Options 1/2 – One 2-lamp ballast 1/3 – One 3-lamp ballast 1/21 – 2-lamp & 1-lamp ballasts EB – Electronic ballast, <20% THD EB95 – T5 electronic ballast, .95 ballast factor EB115 – T5 electronic ballast, 1.15 ballast factor EBSD95 – T5 electronic step dimming ballast, .95 ballast factor EBSD115 – T5 electronic step dimming ballast, 1.15 ballast factor EB101 – Electronic ballast, instant start, <10% THD EB10R – Electronic ballast, program rapid start, <10% THD EBD – Electronic dimming ballast E1 – DEB-1 emerg. ballast, CF only, 350-450 lumens E7 – DEB-7 emerg. ballast, 390-700 lumens E5 – DEB-5 emerg. ballast, CF only, 900 lumens E5ST – DEB-5ST emerg. ballast with self test, CF only, 1100-1400 lumens E7LP – DEB-7LP emerg. ballast, T8/T5/T5HO, 430-700 lumens E6LP – DEB-6LP emerg. ballast, T8/T5/T5HO, 750-1325 lumens F1 – Installed flex, 3/8" diameter, 18 gauge, 3 wire, 6' F2 – Installed flex, 3/8" diameter, 18 gauge, 4 wire, 6' GLR# – Fusing, fast blow (# = number of ballasts) LPT835 – Installed lamps, 80+ CRI, 3500K LPT835HL – Installed T5 hi lumen lamps, 80+ CRI, 3500K (See page 185 for other lamps)	Lamp Type/Wattage 14 – 14W T5 (22") 24HO – 24W T5HO (22") 28 – 28W T5 (46") 54HO – 54W T5HO (46") CF40 – 40W T5 (24") CF50 – 50W T5 (24") CF55 – 55W T5 (24")	Voltage 120 277 347 UNV – Universal voltage, 120-277 volt
	Ceiling Type G – Grid** Refer to pages 192-196 for detailed ceiling information.					

*See pages 184-185 for a complete list of ballast and lamp options including high performance and energy saving choices.

See pages 182-188 for option info. See pages 198-201 for ballast and lamp info.

For matching sconces, see p. 42-44.

For more information concerning Arioso Essence, consult specification sheets 0275-AR, 0276-AR, 0277-AR, and 0278-AR at www.daybrite.com. See page 206 for warranty and lamp disposal information. Data subject to change without notice.