www.etiled.us

Round Flush Mount

LED

22 Watt 1700lms Round Flush Mount

Specifications



The ETi 22 watt 1700 lumen LED round flush mount fixture offers exceptional performance for precision lighting applications, while reducing energy and maintenance cost when compared with conventional light sources. Lasting over 10 times longer, these flush mount fixtures are high quality replacements for incandescent flush mount fixtures and is available in 4000°K. They are UL listed for use in damp and dry locations. ENERGY STAR rated

KEY FEATURES & BENEFITS

- Includes high quality ETi ANSI 4000°K LEDs
- Robust acrylic lens
- Replaces most applications using 150w incandescent lamps
- Concealed 3 point lens mounting bracket
- Rated life 30,000 hours
- Warranty 3 years



This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, please see www.etiled.us/fcc15b

APPLICATION INFORMATION

Designed to be used anywhere a standard incandescent fixture is used. Typically used in bedrooms, hallways, kitchens, living rooms and recreational rooms. The LED round flush mount fixture carries a 3 year warranty.



ET SOLID STATE™ LIGHTING INC

SKU# 54075142

Dimension A = 16.0"

Dimension B = 4.6"

855-384-7754 www.etiled.us

В

FIXTURE DIMENSIONS

Round Flush Mount

LED

SPECIFICATION DATA

Project ______

Item Number_____

Prepared by_____Date_____

ORDERING INFORMATION

ltem Number	Description	Wattage	Input Voltage (VAC)	Average Rated Life ¹	Typical Lumens ²	CCT ³	CRI⁴	Power Factor	R9	Duv	CBCP	Beam	Operating Frequency
E 407E 4 40	LED22w FLUSH- MOUNT 840100-277		400.077	00.000	1700	400.014	00		00.0	0011	170	400	50/0014
54075142	NDIM	22	100-277	30,000	1700	4000K	82	>.95	28.6	.0011	472	120	50/60Hz
¹ Hours life	time with 70	0% lumen	mainten	ance									
² Thermally	/ stable typi	cal lumen	is (±10%))									
³ Thermally	/ stable CC	T (±10%)											
⁴ Color ren	dering index	k/Ra											

SHIPPING INFORMATION

ltem	ltem UPC	Item Dimensions	0		Inner Carton	Inner Carton Dimensions	Weight		Carton	Master Dimen- sions	Master Pack
Number 54075142	836607 008824		(lbs) 2	Qty N/A	Bar Code N/A	(H x L x W)	(lbs) N/A	Qty 4	Bar Code 50836607 008829	(H x L x W) 21.2" x 18.3" x 17.7"	Weight (lbs)

Light Output (Lumens) Watts	17
Lumens per Watt (Efficacy)	
Color Accuracy Color Rendering Index (CRI)	fault
Light Color Correlated Color Temperature (OCT) 4000	(Bright White
Warm White Bright White 2700K 3000K 4500K	Daylight 654
All results are according to ESNA LM-79-2008: Approved M Photometric Teating of Solid-State Lighting: The U.S. Depart product test data and results.	
Visit www.lightingfacts.com for the Label	Reference Guide.
Residuation Number: YN64-NBNSJS (10/16/2012)	
Viotel Number: 540751XX XX modifile 41.50	

The Americas Headquarters 26650 Renaissance Parkway, STE 6 Cleveland, OH 44128

855-384-7754 www.etiled.us

54075142 updated 2/17/2013