

MultiMaster™ Series Precision MultiMeters

500,000 / 50,000 count, High accuracy, Wide bandwidth AC+DC True RMS multimeters

Features:

- 0.02% (MM570) and 0.03% (MM560) basic DCV accuracy
- 50,000 count (500,000 for DCV and Hz) backlit LCD display with bargraph
- Filtered frequency function with adjustable trigger levels for variable speed motor drives and high voltage applications
- Special True RMS combination AC+DC function for measurements of rectified AC (non-symmetrical) voltage & current waveforms
- AC/DC current to 10A with 0.01µA resolution
- 4 to 20mA, displayed as 0-100% for process current measurements
- Max/Min recording with autoranging
- Capacitance, Frequency, Resistance, Continuity, Duty cycle and Diode tests
- High resolution to 1µV, 0.0001Hz, 0.01Ω, 0.01µA and 0.1°
- dBm measurements with 20 selectable impedances
- Features include Auto Power off, Relative & Hold
- Peak function captures transient pulses
- On power-up, meter defaults to last set function
- Audible and visible test lead misconnection warning
- Optional Windows® 95/98/NT/2000/ME/XP compatible PC communication software and optically isolated cable
- Complete with test leads, Type K thermocouple probe (-58 to 482°F/-50 to 250°C)(MM570), protective holster with stand and 9V battery



CAT IV - 600V

Specifications	Range	Max. Resolution	Basic Accuracy (%rdg+digit)
DC Voltage:	500mV, 5V, 50V, 500V, 1000V	0.001mV	±(0.02% + 2d) MM570 ±(0.03% + 2d) MM560
AC Voltage:	500mV, 5V, 50V, 500V, 1000V	0.01mV	±(0.4% + 40d) MM570 ±(0.8% + 30d) MM560
DC Current:	500µA, 5000µA, 50mA, 500mA, 5A, 10A	0.01µA	±(0.1% + 2d)
AC Current:	500µA, 5000µA, 50mA, 500mA, 5A, 10A	0.01µA	±(0.5% + 50d) MM570 ±(1% + 40d) MM560
Resistance (Ω):	500, 5k, 50k, 500k, 5M, 50M	0.01Ω	±(0.07% + 2d) MM570 ±(0.1% + 6d) MM560
Capacitance:	50nF to 9999µF	0.01nF	±(0.8% + 3d)
Line Frequency:	5Hz to 200kHz	0.0001Hz	±(0.008% + 4d)
Logic Frequency:	5Hz to 2MHz	0.0001Hz	±(0.008% + 4d)
Temperature (MM570):	-58 to 1832°F (-50 to 1000°C)	0.1°	±(0.3% + 1°C/2°F)
Duty Cycle:	0.1% to 99.99%	0.01%	±(3d/kHz + 2d)
Dimensions/ Wt:	7.32 x 3.42 x 1.39" (186 x 87x 35.5mm) / 0.75lb (340g)		



Additional Features Model MM560:

- Up to 20kHz True RMS ACV bandwidth
- 600V input protection on all functions (1000V on Voltage)



Additional Features Model MM570:

- Up to 100kHz True RMS ACV bandwidth
- 1000V input protection on all functions
- T1, T2 and T1-T2 dual Type K input temperature display in °F or °C



Optional Windows® 95/98/NT/2000/ME/XP compatible PC communication software and optically isolated cable for data collection.



All models include Double injection molded CAT III - 1000V Test Leads for safety, better grip and added durability.

Ordering Information:

- MM560MultiMaster™ Precision MultiMeter
- MM560-NIST ..MultiMaster™ MM560 with NIST Certificate
- MM570MultiMaster™ Precision MultiMeter with Temperature
- MM570-NIST ..MultiMaster™ MM570 & Temperature with NIST Certificate
- SW810Software Diskette and Serial Cable
- TL805Spare set of CAT III - 1000V Test Leads
- TL807Set of Alligator Clips (2pk) for TL805
- TP872Spare Bead Wire Temperature Probe
- CA899Vinyl Pouch Carrying Case