



4 LONGHORSE 4

LH4-277-L

BALLAST SPECIFICATIONS

UL & cUL APPROVED (E186503) • PATENTED

INPUT


VOLTAGE	277 ± 10% VAC
FREQUENCY	50/60 Hz
MAXIMUM POWER	70 WATT
MAXIMUM CURRENT	.22 AMP
PROTECTION	
• OVER CURRENT	FUSE
• VOLTAGE TRANSIENTS	MOV (PER ANSI C82.11 - 1993)
EMI /RFI	FCC PART 18-A

OUTPUT

OPEN CIRCUIT VOLTAGE	600V RMS MAXIMUM
BALLAST MIN. STARTING TEMP	-20°F
LAMP STARTING / TEMP	INSTANT START / SEE LAMP SPECIFICATIONS
PROTECTION	
• OPEN LAMP	YES
• SHORTED LAMP	YES

APPLICATION / MECHANICAL

RATED	TYPE 1or 2 OUTDOOR
BLACK / WHITE WIRES	18 INCHES
RED POWER WIRES	36 INCHES
YELLOW POWER WIRE	36 INCHES
BALLAST SIZE	H 1", W 1-3/4", L 9-1/2"
BALLAST WEIGHT	24 OZ
CASE QUANTITY	50 BALLASTS
CASE WEIGHT	75 lbs



LAMP COVERAGE

WHEN OPERATED IN ACCORDANCE WITH FULHAM'S WIRING CONFIGURATIONS.

LINEAR LAMPS

T-5
T-5 HO
T-6
T-8

T 10
T-12

ONE OR MORE LAMPS

F4, F6, F8, F13, F14, F21, F28 or F35

F42 or F64
F72

ONE LAMP ONLY

24W or 39W

F13, F14, F15, F17, F18, F25, F30,
F32, or F40
F40
F14, F15, F20, F24, F30, F36, F40,
F42, F48, F60, F64, F72 or F84

Fulham Co., Inc.

10/27/2008

www.Fulham.com

12705 South Van Ness Ave.

Hawthorne, CA 90250

TEL: 1.323.779.2980

FAX: 1.323.754.9060

info@fulham.com

4 LONGHORSE 4

COMPACT LAMPS

BX	5W, 7W, 9W or 11W	13W, 18W, 24W, 27W, 36W, 40W or 50W
FQD		18W, 24W OR 36W
QD	10W, 13W OR 18W	26W
TB	13W	18W, 26W, 32W or 42W
2D	10W	16W, 21W, 28W or 38W
CIRCLINE		20W, 22W or 40W
T-5 CIRCLINE		22W or 40W

Fulham Co., Inc.

10/27/2008
www.Fulham.com

12705 South Van Ness Ave.

Hawthorne, CA 90250

TEL: 1.323.779.2980

FAX: 1.323.754.9060

info@fulham.com