



# 5 LONGHORSE 5


LH5-277-L

## BALLAST SPECIFICATIONS

UL & cUL APPROVED (E186503) • PATENTED

<i>INPUT</i>	
VOLTAGE	277 ± 10% VAC
FREQUENCY	50/60 Hz
MAXIMUM POWER	128 WATT
MAXIMUM CURRENT	.48AMP
PROTECTION	
• OVER CURRENT	FUSE
• VOLTAGE TRANSIENTS	MOV (PER ANSI C82.11 - 1993)
EMI /RFI	FCC PART 18-A
<i>OUTPUT</i>	
OPEN CIRCUIT VOLTAGE	600V RMS MAXIMUM
BALLAST MIN. STARTING TEMP	-20°F
LAMP STARTING / TEMP	INSTANT START / SEE LAMP SPECIFICATIONS
PROTECTION	
• OPEN LAMP	YES
• SHORTED LAMP	YES

<i>APPLICATION / MECHANICAL</i>	
RATED	TYPE 1 OR 2 OUTDOOR
BLACK / WHITE WIRES	18 INCHES
RED POWER WIRES	36 INCHES
YELLOW POWER WIRE	36 INCHES
BALLAST SIZE	H 1", W 1-3/4", L 13.3"
BALLAST WEIGHT	26.4 OZ
CASE QUANTITY	25 BALLASTS
CASE WEIGHT	41.25 lbs



### LAMP COVERAGE

WHEN OPERATED IN ACCORDANCE WITH FULHAM'S WIRING CONFIGURATIONS.

<i>LINEAR LAMPS</i>	<i>ONE OR MORE LAMPS</i>	<i>ONE LAMP ONLY</i>
T-5 HO	F24, F39 OR F54	F80
T-8	F13, F14, F15, F17, F18, F25, F30, F32 or F40	F70
T-8 HO	F48, F60 or F72	
T-10	F40	
T-12	F14, F15, F20, F24, F25, F30, F36, F40, F42, F48, F60, F64, F72, F84 or F96 (60W)	F96 (75W/60W)
T-12 HO		F18, F24, F30, F36, F42, F48, F60, F64, F72, F84 or F96

**Fulham Co., Inc.**

10/27/2008

www.Fulham.com

12705 South Van Ness Ave.

Hawthorne, CA 90250

TEL: 1.323.779.2980

FAX: 1.323.754.9060

info@fulham.com

## 5 LONGHORSE 5

### COMPACT LAMPS

BX  
FQD  
QD  
TB  
2D  
CIRCLINE  
T-5 CIRCLINE

### ONE OR MORE LAMPS

5W, 13W, 18W, 24W, 27W, 28W,  
36W/39W, 40W, 50W or 55W  
18W, 24W or 36W  
18W or 26W  
18W, 26W, 32W or 42W  
16W, 21W, 28W or 38W  
20W, 22W, 32W or 40W  
22W, 40W OR 55W

### ONE LAMP ONLY

55W(PA) OR 96W  
28W, 55W or 96W  
27W  
55W  
22W + 32W or 32W + 40W  
22W + 40W

**Fulham Co., Inc.**

10/27/2008  
www.Fulham.com

12705 South Van Ness Ave.

Hawthorne, CA 90250

TEL: 1.323.779.2980

FAX: 1.323.754.9060

info@fulham.com