



2 WORKHORSE 2

WH2-120-L, C, BLS

BALLAST SPECIFICATIONS

UL & cUL APPROVED (E186503) • PATENTED

INPUT


VOLTAGE	120 ± 10% VAC
FREQUENCY	50/60 Hz
MAXIMUM POWER	35 WATT
MAXIMUM CURRENT	.33 AMP
PROTECTION	
• OVER CURRENT	FUSE
• VOLTAGE TRANSIENTS	MOV (PER ANSI C82.11 - 1993)
EMI /RFI	FCC PART 18-A

OUTPUT

OPEN CIRCUIT VOLTAGE	600V RMS MAXIMUM
BALLAST MIN. STARTING TEMP.	-20°F
LAMP STARTING / TEMP	INSTANT START / SEE LAMP SPECIFICATIONS
PROTECTION	
• OPEN LAMP	YES
• LAMP ALERT	YES
• SHORTED LAMP	YES

APPLICATION / MECHANICAL

RATED	TYPE 1 OR 2 OUTDOOR
BLACK / WHITE WIRES	“C” 12 INCHES
	“L” 18 INCHES
RED / YELLOW POWER WIRES	“C” 18 INCHES
	“L” 36 INCHES
CASE SIZE	“L” H 1”, W 1.25”, L 5.5”
	“C” H 1”, W 1.84”, L 3.35”
BALLAST WEIGHT	“L” 7.2 OZ
	“C” 5.6 OZ
CASE QUANTITY	50 BALLASTS
CASE WEIGHT	“L” 22.5 lbs.
	“C” 17.5 lbs.



LAMP COVERAGE

WHEN OPERATED IN ACCORDANCE WITH FULHAM'S WIRING CONFIGURATIONS

LINEAR LAMPS

T-5
T-5 HO
T-6
T-8

T-12

ONE OR MORE LAMPS

F4, F6, F8, F13, F14 or F21

ONE LAMP ONLY

F 28 or F35
F24
F42 OR F64
F13, F14, F15, F17, F18, F25, F30,
F32 or F72
F14, F15 or F20

Fulham Co., Inc.

3/25/2005
www.Fulham.com

12705 South Van Ness Ave.

Hawthorne, CA 90250

TEL: 1.323.779.2980

FAX: 1.323.754.9060

info@fulham.com

COMPACT LAMPS

BX	5W, 7W, 9W or 11W	13W, 18W, 24W or 27W
FQD		18W, 24W or 36W
QD	10W or 13W	18W or 26W
TB	13W	18W, 26W or 32W
2D	10W	16W, 21W or 28W
CIRCLINE		20W or 22W
T-5 CIRCLINE		22W

Fulham Co., Inc.

3/25/2005
www.Fulham.com

12705 South Van Ness Ave.
Hawthorne, CA 90250

TEL: 1.323.779.2980

FAX: 1.323.754.9060

info@fulham.com