



PRISM®
◀ Halogen PAR

PRISM® Halogen PAR

Energy Efficient

- Halogen technology provides crisp, white light
- More lumens per watt than standard incandescent lamps make PAR halogens the energy efficient choice
- Frosted lamp provides soft light without shadows
- Excellent color rendering

Technical Data

- Heavy-duty 2-piece construction
- Multi-support CC-8 filament
- Nickel-plated brass base

Long Life

- 2,500 Hours Average Rated Life

Applications

- Retail/display lighting
- Accent lighting
- Office building and residential lighting



Spiral lens eliminates striations to provide a consistent, smooth beam pattern.

Call Halco today and get a great look at our vast product line, personal service and fast delivery. Visit us at halcolighting.com.

Your account representative is your single source for pricing, orders, and technical support.

Shipping from Atlanta, Cleveland, Houston, and Phoenix.



**where there's light,
there's halco™**

(800) 677-3334
halcolighting.com

Bulb Type	Watts	Base	Item #	Product Code	Description	Inner/ Master	Volts	Initial Lumens	Avg Rated Life	Filament Design	MOL	Beam Spread
PAR14	35	Med	107548	HP14FL35	Flood	10/40	130	300	2000	CC-8	2-3/8"	30°
PAR16	45	Med	107502	HP16NFL45	Narrow Flood	15	130	440	2500	CC-8	3-5/16"	30°
PAR16	60	Med	107616	HP16NFL60	Narrow Flood	15	130	600	2500	CC-8	3-5/16"	30°
PAR16	60	Med	107850	HP16NFL60/120	Narrow Flood	15	120	600	2500	CC-8	3-5/16"	30°
PAR16	60	Med	107504	HP16NSP60	Narrow Spot	15	130	600	2500	CC-8	3-5/16"	10°
PAR20	35	Med	107610	HP20NFL35	Narrow Flood	15	130	450	2500	CC-8	3-1/4"	30°
PAR20	50	Med	107674	HP20FL50	Flood	15	130	500	2500	CC-8	3-1/4"	40°
PAR20	50	Med	107624	HP20NFL50	Narrow Flood	15	130	500	2500	CC-8	3-1/4"	30°
PAR20	50	Med	107660	HP20NFL50/120	Narrow Flood	15	120	500	2500	CC-8	3-1/4"	30°
PAR20	50	Med	107750	HP20FL50/FR	Frost Flood	15	130	420	2500	CC-8	3-1/4"	-
PAR20	50	Med	107626	HP20SP50	Spot	15	130	500	2500	CC-8	3-1/4"	10°
PAR20	50	Med	107852	HP20SP50/120	Spot	15	120	500	2500	CC-8	3-1/4"	10°
PAR30	50	Med	107520	HP30FL50 (E)	Flood	15	130	550	2500	CC-8	3-9/16"	40°
PAR30	50	Med	107854	HP30FL50/120 (E)	Flood	15	120	550	2500	CC-8	3-9/16"	40°
PAR30	50	Med	107522	HP30FL50L (E)	Flood Long Neck	15	130	550	2500	CC-8	4-3/4"	40°
PAR30	50	Med	107528	HP30SP50 (E)	Spot	15	130	550	2500	CC-8	3-9/16"	10°
PAR30	50	Med	107530	HP30SP50L (E)	Spot Long Neck	15	130	550	2500	CC-8	4-3/4"	10°
PAR30	75	Med	107633	HP30FL75 (E)	Flood	15	130	950	2500	CC-8	3-9/16"	40°
PAR30	75	Med	107670	HP30FL75/120 (E)	Flood	15	120	950	2500	CC-8	3-9/16"	40°
PAR30	75	Med	107758	HP30FL75/FR (E)	Frost Flood	15	130	850	2500	CC-8	3-9/16"	-
PAR30	75	Med	107634	HP30FL75L (E)	Flood Long Neck	15	130	950	2500	CC-8	4-3/4"	40°
PAR30	75	Med	107672	HP30FL75L/120 (E)	Flood Long Neck	15	120	950	2500	CC-8	4-3/4"	40°
PAR30	75	Med	107820	HP30FL75L/FR (E)	Frost Flood Long Neck	15	130	850	2500	CC-8	4-3/4"	-
PAR30	75	Med	107540	HP30SP75 (E)	Spot	15	130	950	2500	CC-8	3-9/16"	10°
PAR30	75	Med	107858	HP30SP75/120 (E)	Spot	15	120	950	2500	CC-8	3-9/16"	10°
PAR30	75	Med	107542	HP30SP75L (E)	Spot Long Neck	15	130	950	2500	CC-8	4-3/4"	10°
PAR30	75	Med	107572	HP30WFL75L (E)	Wide Flood Long Neck	15	130	950	2500	CC-8	4-3/4"	60°
PAR38	45	Med	107564	HP38FL45 (E)	Flood	15	130	500	2500	CC-8	5-3/16"	30°
PAR38	45	Med	107690	HP38FL45/120 (E)	Flood	15	120	500	2500	CC-8	5-3/16"	30°
PAR38	45	Med	107580	HP38SP45 (E)	Spot	15	130	500	2500	CC-8	5-3/16"	10°
PAR38	60	Med	107568	HP38FL60 (E)	Flood	15	130	800	2500	CC-8	5-3/16"	30°
PAR38	60	Med	107754	HP38FL60/FR (E)	Frost Flood	15	130	660	2500	CC-8	5-3/16"	-
PAR38	75	Med	107576	HP38FL75 (E)	Flood	15	130	1000	2500	CC-8	5-3/16"	30°
PAR38	75	Med	107864	HP38FL75/120 (E)	Flood	15	120	1000	2500	CC-8	5-3/16"	30°
PAR38	90	Med	107644	HP38FL90 (E)	Flood	15	130	1250	2500	CC-8	5-3/16"	30°
PAR38	90	Med	107696	HP38FL90/120 (E)	Flood	15	120	1250	2500	CC-8	5-3/16"	30°
PAR38	90	Med	107840	HP38FL90/FR (E)	Frost Flood	15	130	1100	2500	CC-8	5-3/16"	-
PAR38	90	Med	107584	HP38SP90 (E)	Spot	15	130	1250	2500	CC-8	5-3/16"	10°
PAR38	90	Med	107866	HP38SP90/120 (E)	Spot	15	120	1250	2500	CC-8	5-3/16"	10°
PAR38	120	Med	107560	HP38FL120 (E)	Flood	15	130	1800	2500	CC-8	5-3/16"	30°
PAR38	120	Med	107868	HP38FL120/120 (E)	Flood	15	120	1800	2500	CC-8	5-3/16"	30°

(E) Means this lamp meets Federal Minimum Efficiency Standards.

Available at www.GoodMart.com
877-402-6100
Lighting, Electrical, Tools, Datacom