

# MICROLITER® SERIES

Cat. #		Approvals
Job	Type	




## APPLICATIONS

- Signs, facades, small area illumination, flag poles and landscape accent

## SPECIFICATIONS

- Die cast aluminum housing is rugged, yet lightweight and compact in size
- The die cast aluminum door hinges and is removable for service. Two Hubbell Gard® screw fasteners secure the lens door to a silicone gasket for positive seal
- 1/2" cast aluminum knuckle provides universal aiming (1/2 x 14 NPS)
- Rotatable optics. Medium base lamp included
- HPS offered in 120V NPF or Multitap HPF, PSMH is HPF Multitap
- Bronze Lektrocote® powder paint finish



A	B	C	D	E	F
4 <sup>7</sup> / <sub>8</sub> "	2 <sup>1</sup> / <sub>2</sub> "	9 <sup>1</sup> / <sub>4</sub> "	7 <sup>3</sup> / <sub>8</sub> "	12 <sup>1</sup> / <sub>8</sub> "	9 <sup>1</sup> / <sub>4</sub> "
124 mm	64 mm	235 mm	187 mm	308 mm	235 mm

## LISTINGS

- Listed to UL1598 for use in wet locations



## ORDERING INFORMATION

Catalog Number <sup>1</sup>	Wattage	Photometry NEMA/IES H° x V°	Lamp Type	Voltage	Weight lbs. (kg)	EPA ft² (m²)	Ballast Type <sup>2</sup>
<b>Normal Power Factor, High Pressure Sodium</b>							
<b>MIC-0070S-651</b>	70	5 (90°) x 6 (102°)	Coated	120 NPF	9 (4.1)	0.71 (0.1)	RX
<b>MIC-0150S-651</b>	150	5 (71°) x 3 (34°)	Clear	120 NPF	10 (4.6)	0.71 (0.1)	RX
<b>High Power Factor, High Pressure Sodium</b>							
<b>MIC-0150S-258<sup>3</sup></b>	150	5 (71°) x 3 (34°)	Clear	120/208/240/277	14 (6.4)	0.71 (0.1)	AL
<b>High Power Factor, Pulse Start Metal Halide</b>							
<b>MIC-0070H-358<sup>3</sup></b>	70	5 (81°) x 4 (60°)	Clear	120/208/240/277	11 (5)	0.71 (0.1)	AL
<b>MIC-0100H-358<sup>3</sup></b>	100	5 (86°) x 4 (62°)	Clear	120/208/240/277	13 (5.9)	0.71 (0.1)	AL
<b>MIC-0150P-338<sup>3</sup></b>	150	3 (32°) x 3 (36°)	Clear	120/208/240/277	14 (6.4)	0.71 (0.1)	PLA
<b>MIC-0150P-358<sup>3</sup></b>	150	6 (103°) x 5 (81°)	Clear	120/208/240/277	14 (6.4)	0.71 (0.1)	PLA
<b>Less Ballast - Medium Base Socket</b>							
<b>MIC-XXXX-XXX</b>	Less Ballast	Varies	150 max	None	6 (2.7)	0.71 (0.1)	None


- 1 Lamp included  
 2 Ballasts are Class H, -40°F starting (HPS), -20°F starting (PSMH)  
 3 Quad-Tap® luminaires are shipped wired for 277V, easily changed to other voltages in the field

## ACCESSORIES - Order Separately


Catalog Number	Description
<b>MIC-GS-2</b>	Glare shield (360°) bronze
<b>MIC-TB</b>	Crossarm trunnion box, half yoke with large wiring box for mounting to any flat surface
<b>MIC-SPC-2</b>	Polycarbonate shield assembly
<b>S-302-M51</b>	Pole-top slipfitter for 1/2" knuckle, slipfits 2 3/8" OD pipe, bronze finish
<b>PBT-1</b>	Photocontrol, button type, 120V

## REPLACEMENT PARTS


Catalog Number	Description
<b>264-0292-9903</b>	Lens
<b>800-2827-0100</b>	Bronze lens/door assembly
<b>207-5011-0264</b>	Bronze knuckle



MIC-GS-2



MIC-TB



MIC-SPC-2



S-302-M51



PBT-1



Hubbell Outdoor Lighting • 701 Millennium Boulevard • Greenville, SC 29607 • Phone: 864-678-1000

Due to our continued efforts to improve our products, product specifications are subject to change without notice.

© 2013 HUBBELL OUTDOOR LIGHTING, All Rights Reserved • For more information visit our website: [www.hubbelloutdoor.com](http://www.hubbelloutdoor.com) • Printed in USA

MIC-SPEC 3/13