


# ITV4-LED

MR16 LED Gimbal

<b>Catalog Number</b>	<b>Type</b>
<b>Notes</b>	



\*LED Lamp Must Be Order Separately



## Housing Matrix | Example : ITV4-LEDW-C12W

Series		Finish		Track Connection	
A		B		C	
<b>A</b>	Series	<b>C</b>	Options		
<b>ITV4-LED</b>	Low Voltage MR16 Gimbal Track Head	<b>-C12W</b>	12" Connection White		
		<b>-C12B</b>	12" Connection Black		
		<b>-C12SN</b>	12" Connection Satin Nickel		
<b>B</b>	Finish	<b>-C18W</b>	18" Connection White		
<b>W</b>	White	<b>-C18B</b>	18" Connection Black		
<b>B</b>	Black	<b>-C18SN</b>	18" Connection Satin Nickel		
<b>SN</b>	Satin Nickel				

### Description:

Low voltage MR16 gimbal track luminaire. Ideal for task and accent lighting applications. Integral LED driver.

### Lamp:

MR16-LED 12V 8W max (Not included).

### Socket:

GUS.3 Ceramic Bi Pin

### Features:

- Designed for accent and task lighting
- Lightweight, strong construction
- Clean style
- Adjustable for precision aiming
- One or two circuit track capable
- 355° rotation

### LED Driver:

- Integral LED electronic driver for use with 12V MR-16 LED Lamps.
- Class 2 15W max load driver. Input 120V 50/60Hz. Output 11.7V 40kHz.
- Full range ELV dimming to 10%.

### Track Compatibility:

Track luminaire is designed for use with the following track systems:

- Single Circuit/Single Neutral
- Two Circuit/Single Neutral

As a default, the track adapter is shipped from the factory for use with the single circuit track system.

Positive contact is in the "down" position. Raise contact with a screwdriver or pliers to the "up" position for two circuit compatibility.

### Track Connections Option:

Track connections give the flexibility to put lighting where it is needed. Connections are available with line voltage and select low voltage track heads. Conveniently factory installed, Track Connection are a labor-free alternative. Specify track connection option after track fixture catalog number.

### Listing:

ETL listed to US and Canadian standards for dry locations.

### Warranty:

One (1) year limited warranty after date of shipment. Electronic driver is covered by manufacturer warranty. Consult factory for warranty terms.

# MR16LED Lamps for LED Track Luminaires

<b>Catalog Number</b>	<b>Type</b>
<b>Notes</b>	



<b>MR16 LED GU5.3 Base</b> LED Retrofit Lamps												
Catalog Number	Wattage (W)	Base Type	Input Voltage (V)	Average Rated Life (hrs.) <sup>1</sup>	Typical Lumens (lm) <sup>2</sup>	CCT <sup>3</sup>	CRI <sup>4</sup>	R9	CBCP (CD)	Beam Angle	Power Factor	Dimming
LED6MR16/DIM/830/NFL25	6	GU5.3	12	35,000	300	3000K	87	52	860	25°	-	Yes
LED6MR16/DIM/830/FL36	6	GU5.3	12	35,000	300	3000K	87	38	590	36°	-	Yes
LED6MR16/DIM/827/NFL25	6	GU5.3	12	35,000	240	2700K	85	46	790	25°	-	Yes
LED6MR16/DIM/827/FL36	6	GU5.3	12	35,000	240	2700K	86	54	440	36°	-	Yes

**Notes:** 1. Hours lifetime with 70% lumen maintenance 2. Thermally stable typical lumens (±10%) 3. Thermally stable typical CCT (±10%) 4. CRI – Color Rendering Index