


66-S SERIES PREMIUM LUMINAIRE SURFACE OR PENDANT MOUNTED

Job Name	
Catalog Number	
Notes	Type



application

- A 6 in. by 6 in. surface mount luminaire designed for distinctive architectural interiors
- Ideal for perimeters, hallways, lobbies or other commercial applications where modern direct or bi-directional lighting may be utilized
- Able to be surface or pendant mounted individually or in continuous rows
- Available in various lamp/ballast combinations, optional bi-directional lighting and numerous louver options

finish

- Prior to painting, all metal parts are treated with a multi-stage phosphate bonding process to ensure adhesion and inhibit rusting
- Painted with a lighting grade baked white enamel, having a reflectance factor exceeding 87% for premium quality and durability
- Custom colors are available, consult factory for minimum quantities and lead-time

construction

- The 66-S series is a premium fluorescent luminaire designed for long-term installations
- Features durable steel bodies, quality paint finishes and superior electrical components
- Bodies are die formed from code gauge cold rolled steel and welded together for strength and uniformity
- Full wireway front is die formed for durability and attaches easily with screws
- Ample knockouts are provided on back and ends for convenient installation and continuous through wiring
- Optional apertures for 12% uplighting or complete indirect lighting is available
- All fixtures are U.L. listed and IBEW union made

electrical

- All electrical components are U.L. listed .
- Electronic Class P, thermally protected ballasts standard
- Numerous options are available: see ordering information on back

diffuser

- Low brightness, 100% virgin acrylic clear prismatic lens is standard, consult ordering guide for optional diffusers and louvers
- Standard prismatic lens provides high efficiency with maximum visual comfort and uniform light diffusion
- Easy "lift-and-shift" design for lamping and maintenance

ordering guide

NOTE: SOME ORDERING OPTIONS APPEAR ON PRODUCT LINE.
FOR OTHER OPTIONS, SEE LIST AT RIGHT.

SAMPLE ORDER NUMBER



SERIES NO. WATTAGE TANDEM MOUNT BALLAST TYPE VOLTAGE LENS OPTIONS DIMENSIONS LAMP TYPE
LAMPS OPTIONS 1 2


T-8 ORDERING GUIDE											
66	1, 2, 3	17		S, SU, SI	E8	1, U	PA			6" x 24"	F17T8
66	1, 2, 3	25		S, SU, SI	E8	1, U	PA			6" x 36"	F25T8
66	1, 2, 3	32		S, SU, SI	E8	1, U	PA			6" x 48"	F32T8
66	1, 2, 3	25	T	S, SU, SI	E8	1, U	PA			6" x 72"	F25T8
66	1, 2, 3	32	T	S, SU, SI	E8	1, U	PA			6" x 96"	F32T8

*Note: Tandem units contain double the amount of lamps shown

dimensional data



NOTE: SPECIFICATIONS AND DIMENSIONAL DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

cross sections



back knockout plans and lengths

End View



UPLIGHT PATTERN: AVAILABLE ON FACE DOWN TYPE UNITS ONLY

66-S

SERIES
PREMIUM
LUMINAIRE
SURFACE OR PENDANT MOUNTED

options

OPTIONS: INSERT APPROPRIATE CODE FOR CUSTOMIZED ORDERING

BALLAST

E8 Electronic T8
ED Electronic dimming
(Consult Factory)

NOTE: In order to achieve rated lamp life, fixtures controlled by motion sensors should be ordered with programmed start ballasts when available and minimum time delay should be set to 15 minutes - Consult Factory

VOLTAGE

1 120V
U Universal 120 - 277V

GENERAL OPTIONS

EM Emergency pack, 1 lamp
90 min. up to 500 lu.
2C 2 Circuit

LIGHTING OPTIONS

S Standard surface or pendant mount
SU Surface with uplite apertures
SI Surface indirect

LENS & LOUVER OPTIONS

PA Prismatic acrylic
CW White cross baffle
PS Parabolic silver baffle
S1 Nominal .75 X .75 silver louver
S2 Nominal 1.5 X 1.5 silver louver

accessories

Canopy Standard white 5" dia.,
1 1/2" deep with hardware
Stem Stem + Length needed

LAMP OPTIONS

12 T8 741K
15 T8 735K
10 T8 730K
13 T8 841K
16 T8 835K
11 T8 830K

Revised
5/09

LAMAR LIGHTING 485 Smith Street, Farmingdale, NY 11735 • Tel (631) 777-7700
Fax (631) 777-7705 • Outside NY (800) 724-7743 • www.lamarlighting.com

Lamar
Lighting
Company, Inc.