

# SB3

## SERIES

### PREMIUM

### SURFACE MOUNT

### PARABOLIC

#### *application*

- Clean, architecturally appealing, parabolic unit with superior detailing and finish
- Ideal for commercial and institutional surface mount application
- Able to be surface or pendant mounted individually or in continuous rows
- Available in numerous sizes and lengths, and various lamp/ballast combinations

#### *finish*

- Prior to painting, all metal parts are treated with a multi-stage phosphate bonding process to ensure adhesion and inhibit rusting
- Painted with a lighting grade baked white enamel, having a reflectance factor exceeding 87% for premium quality and durability

#### *construction*

- The SB3 series is a premium, surface mount parabolic unit with heavy-duty construction for stylish long-term use
- Features durable steel bodies, quality paint finishes and superior electrical components
- Die formed from cold rolled steel for strength and uniformity.
- Corners are internally overlapped and welded for crisp appearance, no light leakage and rigidity
- Ballast covers easily removed without tools
- Wiring components are secured to the back housing, allowing removal of the cover for easy maintenance, without disturbing any wiring
- Knockouts provided on top of housing for individual surface mounting and convenient wiring; optional stem or continuous row mounting available
- All fixtures are U.L. listed and IBEW union made

#### *electrical*

- All electrical components are U.L. listed
- Ballasts are class P, thermally protected
- 120V high power factor, energy saving ballasts comply with Federal Energy Efficiency Standards and are standard on all 4 ft. units
- Numerous options are available: T8 electronic, bi-x or dimming; see ordering information on back

#### *louver*

- Constructed of non-corrosive semi-specular anodized aluminum to help reduce glare
- Nominal 3 in. deep louvers provide efficient light distribution and maximize light output in the 30-60 degree zone
- Retained in the fixture by two inconspicuous latches for easy removal when cleaning or relamping
- Latching and hinging is reversible; the louver is removable without tools
- Optional matte black reveal conceals louver hardware and provides a floating effect

## ordering guide

NOTE: SOME ORDERING OPTIONS APPEAR ON PRODUCT LINE.  
FOR OTHER OPTIONS, SEE LIST AT RIGHT.

SAMPLE ORDER NUMBER



SERIES NO. WATTAGE SIZE BALLAST VOLTAGE LOUVER OPTIONS DIMENSIONS LAMP TYPE  
LAMPS TYPE 1 2

### T-12 ORDERING GUIDE

SB3	2	40	14	M2	1, 7	08			12 x 48	F40T12
SB3	2	40	22	M2	1, 7	09			24 x 24	FB40T12/6
SB3	2, 3, 4	40	24	M2	1, 7	18			24 x 48	F40T12


### T-8 ORDERING GUIDE

SB3	2	32	14	E8	1, 7	08			12 x 48	F32T8
SB3	2	32	22	E8	1, 7	09			24 x 24	FB32T8/6
SB3	2, 3, 4	32	24	E8	1, 7	18			24 x 48	F32T8

## dimensional data

NOTE: SPECIFICATIONS AND DIMENSIONAL DATA ARE SUBJECT  
TO CHANGE WITHOUT NOTICE.

### cross sections and back plans



## photometric data

SEE SECTION "P"  
FOR PHOTOMETRIC DATA

Revised  
2/03

# SB3 SERIES PREMIUM SURFACE MOUNT PARABOLIC

## options

OPTIONS: INSERT APPROPRIATE CODE FOR  
CUSTOMIZED ORDERING

### BALLAST

M2	Magnetic T12
MP	Magnetic HPF
E8	Electronic T8
EB	Electronic bias
MB	Magnetic bias
EDX	Electronic dimming Advance MX
MDA	Magnetic dimming Advance *

### VOLTAGE

1	120V
7	277V
U	Universal 120 - 277V

### GENERAL OPTIONS

EM	Emergency pack, 1 lamp 90 min. up to 500 lu.
2C	2 Circuit
2B	2 Bodies
LT	Low temperature ballast
BR	Matte Black Reveal
Canopy	Standard white 5" dia., 1 1/2" deep with hardware
Stem	Stem + Length needed

Stem mounting must be specified  
when ordering.  
\* Other dimming ballasts available  
Consult Factory

## louver options

08	3" deep 1X4 8 cell aluminum louver
16	3" deep 1X4 16 cell aluminum louver
09	3" deep 2X2 9 cell aluminum louver
12	3" deep 2x2 or 2x4 12 cell aluminum louver
16	3" deep 2x2 16 cell aluminum louver
18	3" deep 2x4 18 cell aluminum louver
24	3" deep 2x4 24 cell aluminum louver
32	3" deep 2x4 32 cell aluminum louver

White and full specular louvers are  
available.  
Consult Factory for minimum quantities  
and lead time.

## accessories

### LAMP OPTIONS

12	T8 741K
15	T8 735K
10	T8 730K
13	T8 841K
16	T8 835K
11	T8 830K



**LAMAR LIGHTING** 485 Smith Street, Farmingdale, NY 11735 • Tel (631) 777-7700  
Fax (631) 777-7705 • Outside NY (800) 724-7743 • www.lamarlighting.com