

Job Name

Catalog Number

Notes Type



# application

- Versatile, aesthetically appealing recessed lighting fixture with a perforated metal diffuser creating a direct/indirect center light source for soft, even illumination
- An attractive alternative to standard recessed lighting or where indirect lighting is desired but ceiling heights are too low for pendant mounted fixtures
- Available with lamp and ballast combinations to fit your specific application

# finish

- Prior to painting, all metal parts are treated with a multi-stage phosphate bonding process to ensure adhesion and inhibit rusting
- Painted with a lighting grade baked white enamel, having a reflectance factor exceeding 87% for premium quality and durability

### construction

- The LIC series is a premium, recessed unit with heavy-duty construction for stylish long-term use
- Manufactured from New York City code (20 ga.) steel
- End plates are securely attached by rivets
- Ample knockouts are provided on back and sides for convenient installation
- Access plate is provided with two 7/8" KO and provisions for grounding
- All fixtures are U.L. listed and IBEW union made

# electrical

- All electrical components are U.L. listed
- Electronic Class P, thermally protected ballasts standard
- Numerous options are available: see ordering information on back
- Optional battery backup available for one or two light emergency operation at various output levels; please consult factory for your specific emergency pack requirements

# basket/reflector

- Reflector is constructed of high reflective non-yellowing matte white sheet aluminum for soft, indirect illumination
- Standard center basket is perforated formed steel with approximately 45% light transmission; optional patterns and aperture sizes are available; consult factory
- Basket is retained in fixture by four concealed studs for easy removal when cleaning or re-lamping
- Center basket also available in solid materials, custom colors; consult factory





#### SOME ORDERING OPTIONS APPEAR ON PRODUCT LINE. ordering guide FOR OTHER OPTIONS, SEE LIST AT RIGHT. SAMPLE ORDER NUMBER LICH2 22 40 EB OPTIONS NO. LAMPS WATTAGE SIZE **BALLAST TYPE DIMENSIONS** LAMP TYPE **VOLTAGE** T-8 ORDERING GUIDE 2, 3 22 1, 7, U 24" x 24" F17T8 E8 BIAX ORDERING GUIDE 2, 3 40, 50, 55 24" x 24" F40TT, F50TT, F55TT 22 EΒ 1, 7, U T5 ORDERING GUIDE LIC 2, 3 14, 24 22 E5, H5 1, 7, U 24" x 24" F14T5/ F24T5HO


dimensional data

NOTE: SPECIFICATIONS AND DIMENSIONAL DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

# cross sections








END VIEW Biax

END VIEW T5



END VIEW T8

Revised 11/07

**LAMAR LIGHTING** 485 Smith Street, Farmingdale, NY 11735 • Tel (631) 777-7700 Fax (631) 777-7705 • Outside NY (800) 724-7743 • www.lamarlighting.com



# options

OPTIONS: INSERT APPROPRIATE CODE FOR CUSTOMIZED ORDERING

#### BALLAST

E5 Electronic T5
H5 Electronic T5 H0
E8 Electronic T8
EB Electronic Biax
ED Electronic Dimming
(Consult Factory)

### **VOLTAGE**

120V

277V

U Universal 120 - 277V

#### **GENERAL OPTIONS**

EM Emergency pack, 1 lamp 90 min. up to 500 lu.

2C 2 Circuit

PF Round center basket-perforated

(Standard)

B Round center basket-solid

Consult Factory for additional options not shown or listed

### accessories

W 6 ft. 3-wire whip

#### **LAMP OPTIONS**

12 T8 741K 15 T8 735K 10 T8 730K 13 T5/T8 841K 16 T5/T8 835K 11 T5/T8 830K

