

LICS SERIES

RECESSED
STYLING
2 X 4
INDIRECT
LAY-IN
CENTER
BASKET WITH
SLOT

Job Name

Catalog Number

Notes

Type



application

- Versatile, aesthetically appealing recessed lighting fixture with a perforated metal diffuser creating a direct/indirect center light source for soft, even illumination
- An attractive alternative to standard recessed lighting or where indirect lighting is desired but ceiling heights are too low for pendant mounted fixtures
- Available with lamp and ballast combinations to fit your specific application

finish

- Prior to painting, all metal parts are treated with a multi-stage phosphate bonding process to ensure adhesion and inhibit rusting
- Painted with a lighting grade baked white enamel, having a reflectance factor exceeding 87% for premium quality and durability

construction

- The LICS series is a premium, recessed unit with heavy-duty construction for stylish long-term use
- Manufactured from code gauge steel
- End plates are securely attached by rivets
- Ample knockouts are provided on back and sides for convenient installation
- Access plate is provided with two 7/8" KO and provisions for grounding
- Slot grid construction available - see ordering information on back
- All fixtures are U.L. listed and IBEW union made

electrical

- All electrical components are U.L. listed
- Electronic Class P, thermally protected ballasts standard
- Numerous options are available: see ordering information on back
- Optional battery backup available for emergency operation at various output levels; please consult factory for your specific emergency pack requirements

basket/reflector

- Reflector is constructed of high reflective non-yellowing matte white sheet aluminum for soft, indirect illumination
- 2 piece center basket is perforated formed steel with approximately 45% light transmission
- Basket is retained in fixture by four concealed studs for easy removal when cleaning or re-lamping
- Optional 2 piece solid center baskets

LaMar
Lighting
Company, Inc.

ordering guide

NOTE: SOME ORDERING OPTIONS APPEAR ON PRODUCT LINE.
FOR OTHER OPTIONS, SEE LIST AT RIGHT.

SAMPLE ORDER NUMBER

LICS 2 32 24 E8 U


SERIES NO. WATTAGE SIZE BALLAST TYPE VOLTAGE OPTIONS DIMENSIONS LAMP TYPE
LAMPS 1 2

T-8 ORDERING GUIDE									
LICS	2, 3	32	24	E8	1, 7, U			23.75" x 47.75"	F32T8
BIAx ORDERING GUIDE									
LICS	4	40, 50, 55	24	EB	1, 7, U			23.75" x 47.75"	F40TT, F50TT, F55TT
T5 ORDERING GUIDE									
LICS	2, 3	28, 54	24	E5, H5	1, 7, U			23.75" x 47.75"	F28T5/F54T5HO

dimensional data



NOTE: SPECIFICATIONS AND DIMENSIONAL DATA ARE SUBJECT
TO CHANGE WITHOUT NOTICE.

cross sections




Optional 3rd lamp

END VIEW
T8



Optional 3rd lamp

END VIEW
Biax



Optional 3rd lamp

END VIEW
T5

LICS

SERIES
RECESSED
INDIRECT 2X4 LAY-IN

options

OPTIONS: INSERT APPROPRIATE CODE FOR
CUSTOMIZED ORDERING

BALLAST

E5 Electronic T5
H5 Electronic T5 HO
E8 Electronic T8
EB Electronic biax
ED Electronic Dimming
(Consult Factory)

NOTE: In order to achieve rated lamp life,
fixtures controlled by motion sensors should
be ordered with programmed start ballasts
when available and minimum time delay
should be set to 15 minutes - Consult Factory

VOLTAGE

1 120V
7 277V
U Universal 120 - 277V

GENERAL OPTIONS

EM Emergency pack, 1 lamp
90 min. up to 500 lu.
2C 2 Circuit
PF Round center basket - perforated
(Standard)
SB Round center basket - solid
SG Slot grid construction

Consult Factory for additional options not
shown or listed

accessories

W 6 ft. 3-wire whip

LAMP OPTIONS

12 T8 741K
15 T8 735K
10 T8 730K
13 T5/T8 841K
16 T5/T8 835K
11 T5/T8 830K

Revised
4/09

LAMAR LIGHTING 485 Smith Street, Farmingdale, NY 11735 • Tel (631) 777-7700
Fax (631) 777-7705 • Outside NY (800) 724-7743 • www.lamarlighting.com

Lamar
Lighting
Company, Inc.