LUMINES CENT S U S E R I E S



specifications

housing

- One piece die formed steel
- Brushed finish
- Meets ADA requirements
- Low profile, distinctively designed,

lens

- Symmetrically contoured diffuser retained by distinctive accent rings
- Smooth white acrylic

electrical

- Ballast 120 volt Class "P"
- Energy saving compact fluorescent lamp option
- U.L. Listed, IBEW union made
- Indoor use

options

INSERT APPROPRIATE CODE FOR CUSTOMIZED ORDERING

BALLAST

- PN Magnetic normal power factor CFL
- MP Magnetic high power factor CFL
- EP Electronic CFL 4P 2GX7 base
- EQ Electronic CFL 4P quad base
- M9 Circline magnetic normal power factor
- E9 Circline electronic T9
- E5 Circline electronic T5
- OS Integral Infrared Occupancy Sensor

VOLTAGE

- 1 120V
- 7 277V
- U Universal (120/277V) Consult Factory

COLOR

- B Brite brass accent rings consult factory
- N Brushed nickel accent rings Consult Factory for custom finishes

GENERAL OPTIONS

SW Smooth white acrylic lens

Consult Factory for additional options not shown or listed

Fixture meets ADA requirements for wall mounting.



R

Job Name	
Catalog Number	
Notes	Туре



ordering guide

MODEL#	LAMP TYPE	DIAMETER	DEPTH	1	7	PN	MP	EQ/EP	М9	E5
SUN12218M91SW	FC8T9	17 ⁵ / ₈	4	STD	~				STD	
SUN21318PN1SW	(2) CFL13W	17 ⁵ / ₈	4	STD	~	STD	~	~		
SUN31318PN1SW	(3) CFL13W	17 ⁵ / ₈	4	STD	~	STD	~	~		
SUN14018E51SW	FPC40T5	17 ⁵ / ₈	4	STD	~					STD
SUN13218M91SW	FC12T9	17 ⁵ / ₈	4	STD	~				STD	
SUN21818EQ1SW	(2) CFL18W	17 ⁵ / ₈	4	STD	~			STD		
SUN22618EQ1SW	(2) CFL26W	17 ⁵ / ₈	4	STD	~			STD		
SUN25418M91SW	FC8T9 &	17 ⁵ / ₈	4	STD	~				STD	
	FC12T9									

Consult Factory for Emergency Battery Backup options

E9 option available for circline lamps - consult factory



STD Standard

Available option

EP - 13W ONLY

LAMAR LIGHTING 485 Smith Street, Farmingdale, NY 11735 • Tel (631) 777-7700 Fax (631) 777-7705 • Outside NY (800) 724-7743 • www.lamarlighting.com