




Color: White



OSC05-U0W

UPC Code: 07847718054

Country of Origin: China

Description

Ultrasonic, 180 Degree, 500 Sq. Ft. Coverage, Self-Adjusting, Ceiling Mount Occupancy Sensor, Commercial Grade - White.

Product Features

Sensor Type: Ultrasonic

Adjustment: Self-Adjusting

Sensor Technology: Ultrasonic 40kHz

Pattern Degrees: 180

Coverage Range Sq. Ft.: 500

Manual Time Adjustment: 30s-30m, 6s Test Mode

Load Rating: Uses Power Pack

Input Voltage: 24VDC

Current Consumption: 30mA

Photo Cell: Ambient Override ON

Color: White

Standards and Certifications: CUL/US Cert

Warranty: 5-Year Limited

Housing Material: High-Impact, Injection Moulded Plastic

Code Compliance: California Title 24

Features and Benefits

- **Small Size:** Installed sensor appears almost invisible.
- **Fast Simple Installation:** Easy ceiling mount, three wire connection (low voltage) and twist-lock sensor attachment.
- **Accurate, Consistent Switching:** Occupant complaints are eliminated; lights are on when room is occupied, off when empty. annoying false-offs are minimized and lights on at night is eliminated.
- **Self-Adapting:** An internal microprocessor continually analyzes, evaluates and adjusts settings. Performance is kept at a maximum and user complaints are eliminated.
- **Maximum Reliability, Low Cost:** All digital circuitry uses a minimum of components.
- **Non-Volatile Memory:** Learned and adjusted settings saved in protected memory. Power outages will not cause status loss.
- **Ambient Light Recognition:** The photocell prevents lights from turning on when room is adequately lit by natural light.
- **Excellent Warranty:** 5-Year Limited warranty.
- **Typical Applications:** Cafeteria, Computer Room, Office w/Cubicles, File Room, Partitioned Restroom, Warehouse Open Area, Work Space General, Workout Facility, Gymnasium, or Hallway

Control Specifications	
Adjustment	Self-Adjusting
Manual Time Adjustment	30s-30m, 6s Test Mode
Timer Factory Preset	10 Minutes
Sensitivity Adjustment	0 to 100 Pct
Sensitivity Factory Preset	Ultrasonic 50 Pct
Photo Cell Adjustment	20 to 3000 Lux
Photocell Factory Preset	3000 Lux (disable photocell)
LED Disable	LEDS Enable/LEDS Disable

Environmental Specifications	
Operating Temperature	32F to 104F 0C to 40C
Operating Humidity	0 Pct to 95 Pct Relative, Non-Condensing

Mechanical Specifications	
Sensor Technology	Ultrasonic 40kHz
Pattern Degrees	180
Coverage Range Sq. Ft.	500
Major Motion Area	23X23 Feet
Minor Motion Area	17X17 Feet
Photo Cell	Ambient Override ON

Electrical Specifications	
Input Voltage	24VDC
Current Consumption	30mA
Output Voltage	24VDC w/Short Circuit Protection
Load Rating	Uses Power Pack

Material Specifications	
Color	White
Housing Material	High-Impact, Injection Moulded Plastic
LED Indicator	Green Ultrasonic Motion
Qty of Transducer Pairs	1
Transducer Size	16 mm Diameter
Wire Leads	Color Coded 6 Inch
Sensor Weight	5oz/142g

Standards and Certifications	
CUL/US	Listed 9034
ANCE	Compliant
NOM	057
Code Compliance	California Title 24
ASHRAE	Standard 90.1 Compliant
FCC	Compliant

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
<input type="text"/>	<input type="text"/>	<input type="text"/>
JOB NUMBER:	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: 1-800-323-8920 · FAX: 1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): 1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: 1-800-469-7890 ·

FAX: 1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 ·

www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2007-2010 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts/

