



Ceiling Opening: 3-3/4" (95mm)

Complete fixture consists of the Housing, Trim and Frame-in Kit. Select each separately.

Reflector Trim		Frame-in Kit	Lamp
346WWHX	White paint flange	Remodeler	37W MR16 IR
346WSTX	Brushed Steel Flange	Remodeler	37W MR16 IR
346WCMX	Chrome plated flange	Non-IC	50W MR16 / 37W MR16 IR
		Non-IC	50W MR16 / 37W MR16 IR
		IC	50W MR16 / 37W MR16 IR
		IC / AirSeal®	37W MR16
		IC / AirSeal®	37W MR16

Features

- Housing:** 25 ga steel. Black painted finish.
- Residence Mounting Clips:** Factory-installed; zinc plated spring steel; free-hand installation. (patent # 2,184,149)
- Flange:** Die-cast aluminum 0.060" (1.5mm) thick.
- Reflector:** Steel 24ga painted white, for a uniform light diffusion.
- Mounting Clips (2):** 24 ga. spring steel, zinc plated. Provides easy snap-in / snap-out action.
- Lamp guard:** 2" (51mm) dia. borosilicate glass.
- Lens Support:** Die-cast aluminum 0.125" (3.2mm) thick. Painted black.
- Asymmetric Lens:** Soda-lime temper glass frosted on one side

Note: For complete Frame-in Kit specifications, refer to the 300X series Frame-in Kit specification sheets..

Accessories

300XTC Not compatible with all Frame-in Kits. See 300XTC specification sheet.

Labels

CSA, UL Suitable for damp locations.

Job Information

Type:

Job Name:

Cat. No.:

Lamp(s):

Notes: