



Catalog Number	Finish	Lamp	Wattage	Color Temp	Voltage
DMR01SA	Clear, Satin Aluminum Inner Circle	LED	1W	3000K	120-240V

Features

- Heat Sink/Driver Housing:** Die cast aluminum.
- Lens:** Injection molded acrylic sandblasted with clear polished edges, developed for optimum optical output. Decorative aluminum shield.
- Acrylic Mounting Ring:** Die cast aluminum.
- Decorative Light Diffuser:** Die cast aluminum.
- Re-modeler Junction Box:** Die cut and formed 16ga. Galvanized steel. Can be used in new or existing construction.

Electrical

LED: (1) 1W 3000K white LED. Average expected life, under normal operating conditions is 50,000 hours with lumen maintenance of 70% of original light output.

Driver: Integral Class 2 power supply.
Voltage: 120V
Output Wattage: 1 W
Input Current (max.): 65 mA
Frequency: 50/60 Hz
Output Voltage (VDC): 4 V
Constant Current: 350 mA

Finish

Satin aluminum with protective clearcoat.

Labels

cULus Listed. Suitable for Dry Locations

Job Information

Type:

Job Name:

Cat. No.:

Lamp(s):

Notes:

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 www.lightolier.com © 2008 Philips Group • A0608