

LED PAR 38

PARFECTION™ SERIES



PAR 38

Features and Benefits

- Dimmable
- Up to 50,000-hour life
- Up to 85% energy savings compared to halogen
- Thermal-Breeze™ heat sink technology
- Eco-Clear™ optics lens
- Instant-on, instant bright
- Attractive designs, fits in standard fixtures
- Reduces replacement and maintenance costs
- RoHS compliant
- 5-year warranty

Markets

- Restaurants
- Hospitality
- Retail
- Casinos
- Cinema

Applications

- Recessed cans
- Track lighting
- Museums
- Jewelry stores

Litetrronics LED PARFECTION™ Series Light Bulbs - The Greenest Lighting Solution from Litetrronics

Litetrronics LED PARFECTION™ series light bulbs save up to 85% on energy costs, and they are RoHS compliant with mercury-free and lead-free construction, making them the greenest replacement for halogen lighting. Their elegant style maintains the look and shape of an ordinary halogen PAR bulb, and they have the ability to throw a crisp, white beam of light to illuminate brilliant merchandise displays just like halogen bulbs. LED PARFECTION™ bulbs use a patent pending Eco-Clear™ optics lens that generates high center beam candle power in both 15 and 28-degree beam angles. Unlike halogen, LED PARFECTION™ bulbs do not generate ultraviolet, infrared light, or as much heat. This protects displayed items from fading colors and spoiling perishable items that are sensitive to heat.

Compared to competing LED PAR bulbs, LED PARFECTION™ bulbs have higher lumen output and maintain that advantage over their 50,000-hour rated life. This is due to the patent pending Thermal-Breeze™ heat sink design, which allows the LEDs to maintain optimum performance. LED PARFECTION™ bulbs do not need heavy metal heat sinks and actually weigh less than a standard halogen bulb because the Thermal-Breeze™ heat sink provides lower LED temperature to ensure optimum lumen maintenance - even inside recessed ceiling cans. LED PARFECTION™ bulbs' light weight will not exceed the weight capacity of existing fixture and are less costly to ship.

LED PARFECTION™ light bulbs are dimmable with uniform, smooth, dimming control that works on most standard incandescent dimmers. LED PARFECTION™ bulbs can be turned on and off frequently without worrying about bulb life, and they turn on instantly with full lumen output. They are vibration-resistant. This provides improved reliability over CFL, halogen, and incandescent lighting.

LED PARFECTION™ bulbs drastically reduce maintenance and replacement costs, as well as landfill waste, with their 50,000-hour life. Perfectly designed, perfectly green, the Litetrronics LED PARFECTION™ series solves all of your lighting challenges when replacing halogen reflector bulbs.

LITETRONICS®

4101 West 123rd Street
Alsip, Illinois 60803
www.Litetrronics.com

LED PAR 38 *PERFECTION™ SERIES*



PAR 38

LAMP	WATTS	BASE	VOLTS	DESCRIPTION	ORDERING CODE	BEAM ANGLE	BEAM SPREAD	QTY/ CASE	AVERAGE RATED LIFE	CRI	CCT (K)	INITIAL LUMENS	M.O.L.* ₂
PAR 38	10 \$	MED	120	10W PAR38 SP DIM	LP10566SP4D	15°	SPOT	6	50,000	82	3000	600	5.10"
	10 \$	MED	100-240	10W PAR38 SP	LP10566SP4	15°	SPOT	6	50,000	82	3000	600	5.10"
	10 \$	MED	120	10W PAR38 FL DIM	LP10566FL4D	28°	FLOOD	6	50,000	82	3000	600	5.10"
	10 \$	MED	100-240	10W PAR38 FL	LP10566FL4	28°	FLOOD	6	50,000	82	3000	600	5.10"
	15 \$	MED	120	15W PAR38 SP DIM	LP15566SP4D	15°	SPOT	6	50,000	82	3000	850	5.10"
	15 \$	MED	100-240	15W PAR38 SP	LP15566SP4	15°	SPOT	6	50,000	82	3000	850	5.10"
	15 \$	MED	120	15W PAR38 FL DIM	LP15566FL4D	28°	FLOOD	6	50,000	82	3000	850	5.10"
	15 \$	MED	100-240	15W PAR38 FL	LP15566FL4	28°	FLOOD	6	50,000	82	3000	850	5.10"

CONVERSION CHART

LED	=	HALOGEN	=	INCANDESCENT
10-watt	=	50-watt	=	60-watt
15-watt	=	75-watt	=	100-watt

\$ Energy Savings

** Maximum Overall Length (in inches)

