RULIGHTEN NEWS AND INFORMATION

SPIRAL-LITE TM GU24

Compact Fluorescent Lamps



Features and Benefits

- 10,000 hours
- Energy Star qualified
- Up to 80% energy savings compared to incandescent
- 82 CRI
- Small M.O.L. fits more applications
- 1-year warranty

Applications

- · General lighting
- · Table lamps
- · Floor lamps
- · Ceiling fixtures
- Recessed cans

Spiral-Lite GU24 CFLs Provide Long-Lasting Energy Savings

Litetronics Spiral-Lite™ GU24 CFLs are designed for use in GU24 sockets. The GU24 base is only used on energy efficient light sources, such as CFLs. Fixtures with GU24 bases guarantee energy savings over the life of the fixture because inefficient incandescent and halogen lamps are not manufactured with GU24 bases; therefore, they can never be used in the fixture. GU24 fixtures and lamps may be eligible for utility rebates.

Spiral-Lite GU24 CFLs are Energy Star qualified and can save up to 80% on energy costs compared to incandescent lamps. Their 10,000-hour life also offers tremendous financial advanages due to lower maintenance, replacement, and labor costs. All Spiral-Lite GU24 CFLs have a warm 2700K color temperature and come with a 1-year warranty. For long-lasting energy savings, Spiral-Lite GU24 CFLs are the first choice.



4101 West 123rd Street Alsip, Illinois 60803 www.Litetronics.com






LAMP	WATTS	BASE	VOLTS	DESCRIPTION	ORDERING CODE	QTY/ CASE	AVERAGE RATED LIFE	CRI	CORRELATED COLOR TEMP(K)	INITIAL LUMENS	M.O.L.**	M.O.D.***
T3	= 13 \$	GU24	120	13W T3 27 GU24	L-13C27	30	10,000	82	2700	900	3.74"	2.05"
	== 18 \$	GU24	120	18W T3 27 GU24	L-18C27	30	10,000	82	2700	1,300	4.33"	2.12"
	23 \$	GU24	120	23W T3 27 GU24	L-23C27	30	10,000	82	2700	1,725	4.17"	2.44"

SPECIFICATIONS INPUT LINE FREQUENCY 50/60 HZ 5°F - 120°F RELIABLE OPERATING TEMP. **POWER FACTOR** >.50

CONVERSION CHART							
CFL	=	INCANDESCENT					
13-watt	=	60-watt					
18-watt	=	75-watt					
23-watt	=	100-watt					



\$ Energy Savings

** Maximum Overall Length (in inches)

*** Maximum Overall Diameter (in inches)







