

MARK[®]

ARCHITECTURAL LIGHTING



The Duet Series

Featuring one-piece housing with integral louver, Duet is a durable, easy-to-maintain wall-mounted indirect/direct fixture. Baffles can be provided in either regressed or projecting position, and the housing/baffle combination lifts from the wall plate for easy relamping and maintenance.

Duet's compact 4" x 4" profile conforms to the Americans with Disabilities Act (ADA) requirements. It is available in 2-, 4- and 8-foot lengths and can be installed in continuous runs. Finishing end caps that can be attached on-site are provided to terminate runs.

Type:

Project:

Catalog Number:

DO NOT TYPE HERE. Autopopulated field.

Specification Features

Housing

Fabricated from die-formed, 20-gauge, cold-rolled steel. Ballast compartments provided with 7/8"-diameter KOs at either end of housing for through wiring.

Finish

Matte white.

Reflector

Precision-formed steel; white.

Shielding

3/8" high blades at 3/4" on center.

Blades are an integral part of the fixture housing and can be provided in a down position (visible below fixture housing) or in an up position (concealed within housing). Indirect component is provided with an acrylic prismatic lens. Housing

stays on wall and wiring tray lifts out through top to service ballasts.

Lamps

(1) or (2) T5, T5HO or T8 lamps. Lamps provided by others.

Ballast

Thermally protected Class P energy-saving electronic ballast.


Mounting

Wall wash; 4" x 4" x 2', 4' or 8' long. All units are intermediate units and are provided with field-attachable finishing end caps to terminate runs.

Certification

cULus Listed, IBEW (Local 3) Union-made in the USA.

Technical Drawings



Ordering

Example: DUW 4 2T5 EBPR 120 LU

Series		Length		Number of lamps/Lamp type ¹		Ballast		Voltage	Shielding		Options	
DUW	Duet Wall	2	Nominal 2'	Number of lamps	Lamp type ¹	EBPR	Program rapid start (standard)	120	LU	Louver up	EMPK ³	Emergency battery pack
		4	Nominal 4'	1	T5			277				
		8	Nominal 8'	2	T5HO	EBIS	Instant start	347 ²	LD	Louver down	SW ⁴	Soft-white overlay
					T8	EDB	Dimming (specify)					
						EDHL	Lutron Hi-Lume® dimming					
						EDE10	Lutron Eco-10® dimming					
						EDES	Lutron Eco System®					

Notes

- 1 Consult factory for other lamps.
- 2 Consult factory for lamp and ballast compatibility.
- 3 Slim-profile ballasts and slim emergency battery packs only.
- 4 Soft-white overlay for LD shielding only.