

PRODUCT FOCUS

HIGHMAX

Compact Fluorescent Lamp

- FOR >> HIGH & LOW BAYS**
 >> GYMNASIUMS
 >> WALL PACKS
 >> WAREHOUSES
 >> CHURCHES



MAX6257



40W 60W 80W 100W 150W 200W

SKQ40EAWW	SKQ80EAWW	SKO150EAWW
SKQ40EA50	SKQ80EA50	SKO150EA50
SKQ40EA250	SKQ80EA250	SKO150EA250
SKQ40EA350	SKQ80EA350	SKO150EA350
SKQ60EAWW	SKQ100EAWW	SKO200EAWW
SKQ60EA50	SKQ100EA50	SKO200EA50
SKQ60EA250	SKQ100EA250	SKO200EA250
SKQ60EA350	SKQ100EA350	SKO200EA350

- High Lumens (up to 12,000) using less energy
- Long Life - 10,000 Hour[▲]
- Shortened MOL to fit common fixtures
- Self Ballasted / Instant-on
- Available in 120V, 277V and 347V, with edison or mogul base, 2700K and 5000K

▲ MTF - Mean Time to Failure

PRODUCT FOCUS

HIGHMAX

Compact Fluorescent Lamp


SKXE40
 Mogul Adapter
 (7) 6762711259 (1)*

SKQ40EAWW
 10,000 Hour*
 (7) 6762711212 (6)*

SKQ60EAWW
 10,000 Hour*
 (7) 6762711272 (0)*

SKQ80EAWW
 10,000 Hour*
 (7) 6762711275 (1)*

SKQ100EAWW
 10,000 Hour*
 (7) 6762735844 (9)*

SKQ40EA50
 10,000 Hour*
 (7) 6762711211 (9)*

SKQ60EA50
 10,000 Hour*
 (7) 6762711271 (3)*

SKQ80EA50
 10,000 Hour*
 (7) 6762711274 (4)*

SKQ100EA50
 10,000 Hour*
 (7) 6762735840 (1)*

SKQ40EA250
 10,000 Hour*
 (7) 6762711183 (9)*

SKQ60EA250
 10,000 Hour*
 (7) 6762711270 (6)*

SKQ80EA250
 10,000 Hour*
 (7) 6762711273 (7)*

SKQ100EA250
 10,000 Hour*
 (7) 6762735839 (5)*

SKQ40EA350
 10,000 Hour*
 (7) 6762711291 (1)*

SKQ60EA350
 10,000 Hour*
 (7) 6762711292 (8)*

SKQ80EA350
 10,000 Hour*
 (7) 6762711293 (5)*

SKQ100EA350
 10,000 Hour*
 (7) 6762711294 (2)*

HIGHMAX SPECIFICATIONS

Watts	Order Code	Description	Incandescent Equivalent	Lumens	Scotopic Lumens	Efficacy (LM/W)	Lamp Life (Hrs)	Pack Type	Case Pack	Dimensions (W" x MOL")	K
40	11212	SKQ40EAWW 5U 120V E26 HPF	200	3,000	n/a	75	10,000▲	Box	6	3.5 x 8.25	2700
40	11211	SKQ40EA50 5U 120V E26 HPF	200	3,000	5,900	75	10,000▲	Box	6	3.5 x 8.25	5000
40	11183	SKQ40EA250 5U 277V E26 HPF	200	3,000	5,900	75	10,000▲	Box	6	3.5 x 8.25	5000
40	11291	SKQ40EA350 5U 347V E26 HPF	200	3,000	5,900	75	10,000▲	Box	6	3.5 x 8.25	5000
60	11272	SKQ60EAWW 5U 120V E26 HPF	300	4,200	n/a	70	10,000▲	Box	6	3.5 x 9.5	2700
60	11271	SKQ60EA50 5U 120V E26 HPF	300	4,200	8,232	70	10,000▲	Box	6	3.5 x 9.5	5000
60	11270	SKQ60EA250 5U 277V E26 HPF	300	4,200	8,232	70	10,000▲	Box	6	3.5 x 9.5	5000
60	11292	SKQ60EA350 5U 347V E26 HPF	300	4,200	8,232	70	10,000▲	Box	6	3.5 x 9.5	5000
80	11275	SKQ80EAWW 5U 120V E26 HPF	400	5,500	n/a	68	10,000▲	Box	6	3.5 x 10.8	2700
80	11274	SKQ80EA50 5U 120V E26 HPF	400	5,500	10,780	68	10,000▲	Box	6	3.5 x 10.8	5000
80	11273	SKQ80EA250 5U 277V E26 HPF	400	5,500	10,780	68	10,000▲	Box	6	3.5 x 10.8	5000
80	11293	SKQ80EA350 5U 347V E26 HPF	400	5,500	10,780	68	10,000▲	Box	6	3.5 x 10.8	5000
100	35844	SKQ100EAWW 5U 120V E39 HPF	500	6,900	n/a	69	10,000▲	Box	6	3.5 x 12.75	2700
100	35840	SKQ100EA50 5U 120V E39 HPF	500	6,900	13,524	69	10,000▲	Box	6	3.5 x 12.75	5000
100	35839	SKQ100EA250 5U 277V E39 HPF	500	6,900	13,524	69	10,000▲	Box	6	3.5 x 12.75	5000
100	11294	SKQ100EA350 5U 347V E39 HPF	500	6,900	13,524	69	10,000▲	Box	6	3.5 x 12.75	5000
n/a	11259	SKXE40 Mogul Adapter for HighMax									

MAX6257


 FCC Certified
 * UPC Codes

PRODUCT FOCUS

HIGHMAX

Compact Fluorescent Lamp



SKHB27120 10,000 Hour* (7) 6762711243 (0)*	SKHB35120 10,000 Hour* (7) 6762711240 (9)*	SKO150EAWW 10,000 Hour* (7) 6762735862 (3)*	SKO150EA250 10,000 Hour* (7) 6762735863 (0)*	SKO200EAWW 10,000 Hour* (7) 6762735872 (2)*	SKO200EA250 10,000 Hour* (7) 6762735873 (9)*
SKHB27277 10,000 Hour* (7) 6762711244 (7)*	SKHB35277 10,000 Hour* (7) 6762711242 (3)*	SKO150EA50 10,000 Hour* (7) 6762735861 (6)*	SKO150EA350 10,000 Hour* (7) 6762711295 (9)*	SKO200EA50 10,000 Hour* (7) 6762735871 (5)*	SKO200EA350 10,000 Hour* (7) 6762711296 (6)*

HIGHMAX&RETROFIT KIT SPECIFICATIONS

Watts	Order Code	Description	Incandescent Equivalent	Lumens	Scotopic Lumens	Efficacy (LM/W)	Lamp Life (Hrs)	Pack Type	Case Pack	Dimensions (W" x MOL")	K
150	35862	SKO150EAWW 8U 120V E39 HPF	650	9,200	n/a	61.3	10,000▲	Box	6	5 x 13	2700
150	35861	SKO150EA50 8U 120V E39 HPF	650	9,200	18,032	61.3	10,000▲	Box	6	5 x 13	5000
150	35863	SKO150EA250 8U 277V E39 HPF	650	9,200	18,032	61.3	10,000▲	Box	6	5 x 13	5000
150	11295	SKO150EA350 8U 347V E39 HPF	650	9,200	18,032	61.3	10,000▲	Box	6	5 x 13	5000
200	35872	SKO200EAWW 8U 120V E39 HPF	850	12,000	n/a	60	10,000▲	Box	6	5 x 14.5	2700
200	35871	SKO200EA50 8U 120V E39 HPF	850	12,000	23,520	60	10,000▲	Box	6	5 x 14.5	5000
200	35873	SKO200EA250 8U 277V E39 HPF	850	12,000	23,520	60	10,000▲	Box	6	5 x 14.5	5000
200	11296	SKO200EA350 8U 347V E39 HPF	850	12,000	23,520	60	10,000▲	Box	6	5 x 14.5	5000
150	11243	SKHB27120 150W HighMax with inner reflector 27 Foot Candle 120V E39								11 x 9.75	
150	11244	SKHB27277 150W HighMax with inner reflector 27 Foot Candle 277V E39								11 x 9.75	
200	11240	SKHB35120 200W HighMax with inner reflector 35 Foot Candle 120V E39								11 x 9.75	
200	11242	SKHB35277 200W HighMax with inner reflector 35 Foot Candle 277V E39								11 x 9.75	

SPECIAL NOTES

- >> Available with MaxLite's HighBay retrofit kit for retrofitting HID fixtures
- >> Also available with MaxLite's HighMax acrylic highbay fixture for retrofit/new construction
- >> ▲ MTF: Mean Time to Failure
- >> 1 Year warranty from date of purchase. Not suitable for outdoor use

APPLICATIONS

- High & Low Bays
- Gymnasiums
- Warehouses
- Churches
- Wall Packs
- Shop Floors

LOCATIONS

- Commercial
- Retail
- Public Spaces/School
- Parking Garages

BENEFITS

- High Lumens (up to 12,000) using less energy
- Long Life - 10,000 Hours▲
- Shortened MOL to fit common fixtures
- Self Ballasted / Instant-On
- Available in 120V, 277V and 347V, with edison or mogul base, 2700K and 5000K

SPECIFICATIONS

- Ballast Type >> Electronic
- Starting Method >> Modified Rapid Start
- Input Line Voltage >> 120-347VAC
- Input Line Frequency >> 50/60HZ
- Operating Temperature >> 0°-100°F
- Color Rendering Index >> 84


 FCC Certified
 *UPC Codes

Contains Mercury (Hg) Dispose of according to Local, State, and Federal Law / www.lamprecycle.org

MaxLite™ 1-800-555-5629 | Fax: 973-244-7333 | info@maxlite.com | www.maxlite.com