

Type
Project
Catalog No.
Lamp/Wattage

NTH-132LED
Belgium™ Die-Cast Front Loading Gimbal
with LED PAR30
 Lamp: 12W LED PAR30

PRODUCT DESCRIPTION

Line voltage front-loading gimbal fixture. Heavy die-cast construction provides superior strength, rigidity, and heat dissipation. Locking front ring protects lamp and enhances appearance. Front loading capability provides quick, easy lamp maintenance with minimal interference with original fixture aiming.

FEATURES

- Heavy die-cast construction
- Die-cast Lamp Locking Ring
- Fully adjustable, firm angle position
- High-strength stainless steel electrical contacts
- One or two circuit track capable
- Available in J-Style and L-Style

CONSTRUCTION

Housing

0.09" Die-cast aluminum two-piece housing with modernistic detail secured together with finished Allen-head screw. Two arms constructed from thick 0.050" die-cast aluminum extend from the housing and contain molds to secure 0.25" die-cast aluminum locking ring.

Structural Arm

0.10" "L" Steel bracket connects fixture housing to electrical contact head. Two finished plastic knobs allow user to lock fixture position to desired angles.

Socket

Porcelain jacketed aluminum screw thread medium-base socket.

Wiring

Teflon coated wire lead connects socket and housing to electrical contact head. Teflon coating is durable and resists heat degradation from lamp and housing radiation.

Lamp

See LED Lamp Chart below.

Contact Head Assembly

"H" Style (standard): Three 0.030 stainless steel contacts mounted in premium plastic housing.

"J" Style: Two contacts and ground contact mounted in premium plastic housing with on/off switch.

"L" Style: Two contacts and ground contact mounted in premium plastic housing.

Finishes

Black, Silver, or White heat-rated powercoat. Custom painting or anodizing for special applications are also available. Custom finishes will require lead times that vary depending on vendor schedule. Please consult factor for quotation, and provide either a Dunn Edwards number or color chip for exact matching.

One/Two Circuit Conversion


Positive contact (opposite neutral and ground contacts) is preset to "down" position at the factory, but may be raised to the high position to install onto the second circuit of Nora Lighting's NT-2300 series two-circuit track.

Compatibility

Nora track heads are compatible with Halo or any other brands configured to Halo 3 wire track configuration. J-Style and L-Style track adapters are available.

Note: Fixtures may not be compatible with non-Nora monopoint adapters.

DIMENSIONS



Length: 5-1/8"
 Diameter: 4-1/4"
 Max. Extension: 9-3/8"

Labels and Warranty

cULus Listed as track lighting fitting



LED Lamp Chart (Lamps are Energy Star and cULus Listed)

ORDER SUFFIX	KELVIN	WATTS	LUMENS	BEAM ANGLE	CBCP	CRI	RATED LIFE	DIMMABLE
LED PAR30 Short Neck								
E30	2700	12	740	20	5000	83	25K	Yes
E31	3000	12	750	20	5100	84	25K	Yes
E32	2700	12	740	35	2000	83	25K	Yes
E33	3000	12	750	35	2050	84	25K	Yes

Belgium™ Die-Cast Front Loading Gimbal with LED PAR30

Belgium™ Die-Cast Front Loading Gimbal with LED - select one from each column

Catalog No.	Finish	LED Lamp	Contact Head
NTH-132	B = Black	E30 = LED PAR30	(Blank) = H-Style
	S = Silver	E31 = LED PAR30	/J = J-Style
	W = White	E32 = LED PAR30	/L = L-Style
		E33 = LED PAR30	