



Wing Mini Rail Fixture

DESCRIPTION

Low voltage single lamp fixture is aimable 360° in the horizontal plane and reflector rotates 360° in the vertical plane. Both adjustments can be locked in position by loosening set screws and tightening at desired aiming angle.

SPECIFICATION

LAMP

(1) 10W 12V T3 Halogen or Xelogen G4 (included with fixture) or
(1) 10W 24V T3 Xelogen G4

HOUSING

Stainless steel housing composed of three parts: lamp support(stem), lampholder (socket), and reflector (shade).

STEM

Stainless steel threaded U-shaped rail connector supplied with a nut at one end and attached to the cylindrical arm on the other end. Adjustable to 360° in the horizontal plane by loosening set screw and tightening at desired aiming angle.

REFLECTOR

5/8"(16mm) diameter by 1-9/16"(40mm) length stainless steel cylinder with 7/8" (21mm) cut in half which serves as reflector. Adjustable to 360° in the vertical plane by loosening set screw and tightening at desired aiming angle.

WIRING

Internal lead wires are rated 200°C, 300V minimum


SOCKET

Hardened polycarbonate rated 200°C, 300V minimum, enclosed in a stainless steel cylindrical arm.

FINISHES

Available in Bronze(BZ), Chrome (C), Matte Gold (MG), or Matte Nickel (MN)

LABELS

 listed for dry location only.

CATALOG NO.:	TYPE:
PROJECT:	
COMMENTS:	
PREPARED BY:	DATE:

DIMENSIONS

A: Length	2"	(52mm)
B: Diameter	5/8"	(16mm)
C: Max. Extension	1-1/4"	(32mm)

