



## LAMPS

High output red energy efficient LED lamps. Uniform 8" Letter illumination (1" stroke).

## CONSTRUCTION

Housing and canopy constructed of 20 gauge steel. Lamp heads are high impact flame retardant plastic.

## APPROVAL

New York City approved.  
ETL Listed.

## DESIGN

All units supplied with universal housings. Universal mounting-ceiling, end or wall mount, canopy is not required on wall mount. Removable chevron directional indicators (easily removed when required.) Test switch and LED light indicator. 25w unit with 2-9w lamp heads. 36w unit with 3-9. Two to three lamp heads are mounted on front of unit.

## FINISH

White durable powder coat.

## ELECTRONICS

120/277VAC, Dual voltage input, 60hZ Isolated short circuit and voltage protection circuit. Surpasses the 90 minute emergency illumination requirement.

## BATTERY

6 volt sealed maintenance-free lead acid battery.

## WARRANTY

Five full year warranty. (Lamps not Included.)

## CATALOG NUMBER (Example: SCLR3)

<b>SCLRW2</b>	Combo - Red LED, white housing with single white face, 2-9w tungsten lamps
<b>SCLRW3</b>	Combo - Red LED, Single face, white housing with a white face, 3-9w tungsten lamps

Note: When ordering combo without heads, drop number suffix from catalog number.

## OPTIONS

<b>B</b>	Buzzer
<b>DR</b>	Damp Location Rated
<b>SD</b>	Self Diagnostics
<b>F</b>	Flasher
<b>TP</b>	Tamper proof

## ACCESSORIES

<b>WG5</b>	Wire Guard
------------	------------

## DIMENSIONS

Two or Three Heads = 14-1/2" W x 15-1/8" H x 6-1/4" D  
Combo less heads = 14-1/2" W x 15-1/8" H x 2-1/4" D



