Weight: 15.3 lbs

AJF32XQTW

Type II distribution wall mount Area Light with 4" arm for use at 10' - 15' height. Fixed mounting at 90 deg to wall. Lamp supplied.

Lamp Info Ballast Info

Type:	Triple	Type:	Electronic
Watts:	32	120V:	0.3
Shape/Size:	N/A	208V:	0.21
Base:	N/A	240V:	0.16
ANSI:	N/A	277V:	0.13
Hours:	12,000	Input Watts:	36W
Lamp Lumens:	2,400	Efficiency:	89%
Efficacy:	67 LPW		

Technical Specifications

UL Listing:

Suitable for wet locations.

Country of Origin:

Designed by RAB in New Jersey and assembled in the USA by IBEW Local 3

Buy American Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

Recovery Act (ARRA) Compliant:

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-Buy American Act-- Construction Materials (October 2010)

Trade Agreements Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

GSA Schedule:

This product is suitable for listing on the GSA Schedule of the US General Services in accordance with FAR Subpart 25.4

Construction:

Die cast aluminum housing and door. Tether connects door to housing for safety.

Reflector:

High quality hydroformed semi-specular aluminum.


Finish:

Weather resistant polyester powder coat, Architectural Bronze or White finish with stainless steel hardware.

Effective Projected Area:

EPA = 0.8. With House Side Shield = 1.5

Color: White



Patents:

The design of the AJ Area Light is protected by U.S. Patents D579,140, D579,141, D591,445, Canada patents D127,031, D127,040, D127,045, China patents ZL200830143714.3, ZL200830143713.9, ZL200830143712.4, Mexico patents 27395, 28572, 28577 and Taiwan patents D129,808 and D131,622.

Socket:

CFL Plug in type, GX24q-4 base