



# AJH100FXQT/PC



JOB NAME: \_\_\_\_\_  
 DATE: \_\_\_\_\_  
 TYPE: \_\_\_\_\_

## DESCRIPTION

Type II distribution flat wall mount Area Light with 4" arm for use at 10' - 15' height. Fixed mounting @ 90° to wall. Lamp supplied

## SPECIFICATIONS

### Construction:

Die cast aluminum housing and door. Tether connects door to housing for safety.

### Effective Projected Area:

EPA = 0.8. With House Side Shield = 1.5

### Finish:

Weather resistant polyester powder coat, Architectural Bronze or White finish with stainless steel hardware.

### Reflector:

High quality hydroformed semi-specular aluminum.

### UL Listing:

Suitable for wet locations.

### Patents:

The design of the AJ Area Light is protected by U.S. Patents D579,140, D579,141, D591,445, Canada patents D127,031, D127,040, D127,045, China patents ZL200830143714.3, ZL200830143713.9, ZL200830143712.4, Mexico patents 27395, 28572, 28577 and Taiwan patents D129,808 and D131,622.

### Socket:

HID: Porcelain 4KV Pulse rated Medium base. Corrosion resistant screw shell with spring loaded center contact.


### Color:

Bronze

### Weight:

18.87

## DIMENSIONS



## ORDERING INFORMATION

Metal Halide Lamp supplied with fixture	Total Watts	Lamp Type	Lamp Base	Ballast	Starting Amps/ Operating Amps				Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours
					120V	208V	240V	277V				
	100	ED17	Med	HX-HPF QT	1.2/1.2	.8/.7	.7/.6	.6/.5	129	M90	9000	15000

**Factory Installed Options**  
 Add suffix to Catalog Number

Note: Specifications may change without notice