



JOB NAME:	
DATE:	
TYPE:	

## **DESCRIPTION**

Type II distribution Area Light with pole top fixed arm mount for use on 10' - 15' poles. Fixed mounting @ 90° to pole. Drilling 2" on center. Factory wired for 277V. Lamp supplied.

# **SPECIFICATIONS**

#### Construction:

Die cast aluminum housing and door. Tether connects door to housing for safety.

## **Effective Projected Area:**

EPA = 0.8. With House Side Shield = 1.5

### Finish:

Weather resistant polyester powder coat, Architectural Bronze or White finish with stainless steel hardware. Reflector:

High quality hydroformed semi-specular aluminum.

## **UL Listing:**

Suitable for wet locations.

#### Patents:

The design of the AJ Area Light is protected by U.S. Patents D579,140, D579,141, D591,445, Canada patents D127,031, D127,040, D127,045, China patents ZL200830143714.3, ZL200830143713.9, ZL200830143712.4, Mexico patents 27395, 28572, 28577 and Taiwan patents D129,808 and D131,622.

### Socket:

HID: Porcelain 4KV Pulse rated Medium base. Corrosion resistant screw shell with spring loaded center contact.

## Color:

White

## Weight:

17.98

## ORDERING INFORMATION

Metal Halide Lamp supplied with fixture	Total Watts	Lamp Type		Ballast	Starting Amps/ Operating Amps 120V 208V 240V 277V				Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours	
	watts	Type	Dasc	Danast	1201	2001	2401		Watts	AITOI	Lumens	110413	
	70	FD17	Med	HX-HPF OT	7/ 8	3/5	4/4	3/4	91	MOR	5600	15000	

Factory Installed Options
Add suffix to Catalog Number