



JOB NAME:	
DATE:	
TYPE:	

DESCRIPTION

Type II distribution flat wall mount Area Light with 4" arm for use at 10' - 15' height. Fixed mounting @ 90° to wall. Lamp supplied

SPECIFICATIONS

Construction:

Die cast aluminum housing and door. Tether connects door to housing for safety.

Effective Projected Area:

EPA = 0.8. With House Side Shield = 1.5

Finish:

Weather resistant polyester powder coat, Architectural Bronze or White finish with stainless steel hardware. Reflector:

High quality hydroformed semi-specular aluminum.

UL Listing:

Suitable for wet locations.

Patents:

The design of the AJ Area Light is protected by U.S. Patents D579,140, D579,141, D591,445, Canada patents D127,031, D127,040, D127,045, China patents ZL200830143714.3, ZL200830143713.9, ZL200830143712.4, Mexico patents 27395, 28572, 28577 and Taiwan patents D129,808 and D131,622.

Socket:

HID: Porcelain 4KV Pulse rated Medium base. Corrosion resistant screw shell with spring loaded center contact.


Color:

Bronze

Weight:

19.97

DIMENSIONS



ORDERING INFORMATION

High Pressure Sodium	Total	Lamp	Lamp		Starting Amps/ Operating Amps			Input	LAMP	Initial	Lamp		
Lamp supplied with fixture	Watts	Type	Base	Ballast	120V	208V	240V	277V	Watts	ANSI	Lumens	Hours	
	150	FD17	Med	HX-HPF OT	1 6/1 6	a/ a	8/8	9/ 8	188	\$55	16000	24000	

Factory Installed Options Add suffix to Catalog Number

Note: Specifications may change without notice