



JOB NAME:	
DATE:	
TYPE:	

DESCRIPTION

Type II distribution Area Light with wall mount. Fixed mounting @ 90° to wall. Drilling 2" on center. Factory wired for 277V. Lamp supplied.

SPECIFICATIONS

Finish:

Chip and fade resistant bronze polyster powder coat finish.

Housing:

One-piece precision die cast aluminum housing and door held captive when opened. Removable hinge pins for door

removal Lens Gasket:

High temperature extruded silicone set in die cast retaining groove. Remains in place during relamping.

Lens

Thermal, tempered shock resistant glass, 5/32" thick.

Mounting Arm:

Mounts with two 5/16 -18 threaded rods at 2" on center.

Reflector:

Hydroformed Type II reflector.

Patents:

Sensor and fixture designs are protected under U.S. and International Intellectual Property Laws

Socket:

Porcelain socket pulse rated 4kv, 1500 watts and 600 volts, reinforced with cat's eyes for added durability. Silicone and fiberglass #14 gauge socket leads rated for 200° C. Plated screw shell designed to resist corrosion with spring loaded center contact.

UL Listing:

Suitable for wet locations. Suitable for mounting within 4' of the ground.

Color:

White

Weight:

34.66

ORDERING INFORMATION

Metal Halide Total Lamp Lamp Starting Amps/ Operating Amps Input LAMP Initial Lamp 208V 240V Lamp supplied with fixture Watts Type **Ballast** Hours 200 ED28 Mogul CWA HPF QT 1.4/2.0 0.8/1.2 .07/1.0 0.6/0.9 232 M136 19000 15000

 Factory Installed Options
 Swivel Photocontrol (/PCS)

 Add suffix to Catalog Number
 Single fusing for 120 and 27

Single fusing for 120 and 277 volt (/F)
Double fusing for 208 and 240 volt (/FF)

Button Photocontrol (/PC) 480 volt ballast (consult factory) (/480)

Note: Specifications may change without notice