ALH350PSQW

JOB NAME: _____

DATE: _____

TYPE: _____

DESCRIPTION

Type II distribution Area Light with pole top fixed arm mount. Fixed mounting at 90° to pole. Drilling 2" on center. Factory wired for 277V. Lamp supplied.

SPECIFICATIONS

Finish:
Chip and fade resistant bronze polyster powder coat finish.

Housing:
One-piece precision die cast aluminum housing and door held captive when opened. Removable hinge pins for door removal.

Lens Gasket:
High temperature extruded silicone set in die cast retaining groove. Remains in place during relamping.

Lens:
Thermal, tempered shock resistant glass, 5/32" thick.

Mounting Arm:
Mounts with two 5/16 -18 threaded rods at 2" on center.

Patents:
Sensor and fixture designs are protected under U.S. and International Intellectual Property Laws

Reflector:
Hydroformed Type II reflector.

Socket:
Porcelain socket pulse rated 4kv, 1500 watts and 600 volts, reinforced with cat's eyes for added durability. Silicone and fiberglass #14 gauge socket leads rated for 200° C. Plated screw shell designed to resist corrosion with spring loaded center contact.

UL Listing:
Suitable for wet locations. Suitable for mounting within 4' of the ground.

EISA 2007 Compliant
This product complies with the new law for metal halide ballast efficiency. This law goes into effect January 1st, 2008. Pulse Start offers Longer Lamp Life, Faster Startup and Faster Restrike.

EPA:
1

Color:
White

Weight:
34.41

ORDERING INFORMATION

Metal Halide
Lamp supplied with fixture

Total Watts	Lamp Type	Lamp Base	Ballast	Starting Amps/ Operating Amps 120V	208V	240V	277V	Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours
350	ED28	Mogul	CWA HPF QT	3.3/3.6	1.9/2.1	1.7/1.8	1.4/1.6	400	M131	33300	20000

Factory Installed Options
Add suffix to Catalog Number

Swivel Photocontrol (/PCS)
Single fusing for 120 and 277 volt (/F)
Double fusing for 208 and 240 volt (/FF)
Button Photocontrol (/PC)
480 volt ballast (consult factory) (/480)

Note: Specifications may change without notice

RAB Lighting, Inc. • 170 Ludlow Ave• Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • www.rabweb.com
© 2011 RAB Lighting, Inc.