



JOB NAME: \_\_\_\_\_

DATE: \_\_\_\_\_

TYPE: \_\_\_\_\_

# ALH350XPSQW

## DESCRIPTION

Type II distribution Area Light with wall mount. Fixed mounting @ 90° to wall. Drilling 2" on center. Factory wired for 277V. Lamp supplied.

## SPECIFICATIONS

### Finish:

Chip and fade resistant bronze polyester powder coat finish.

### Housing:

One-piece precision die cast aluminum housing and door held captive when opened. Removable hinge pins for door removal.

### Lens Gasket:

High temperature extruded silicone set in die cast retaining groove. Remains in place during relamping.

### Lens:

Thermal, tempered shock resistant glass, 5/32" thick.

### Mounting Arm:

Mounts with two 5/16 -18 threaded rods at 2" on center.

### Reflector:

Hydroformed Type II reflector.

### Patents:

Sensor and fixture designs are protected under U.S. and International Intellectual Property Laws

### Socket:

Porcelain socket pulse rated 4kv, 1500 watts and 600 volts, reinforced with cat's eyes for added durability. Silicone and fiberglass #14 gauge socket leads rated for 200° C. Plated screw shell designed to resist corrosion with spring loaded center contact.

### UL Listing:

Suitable for wet locations. Suitable for mounting within 4' of the ground.

### Color:

White

### Weight:

37.16

## ORDERING INFORMATION

Metal Halide Lamp supplied with fixture	Total Watts	Lamp Type	Lamp Base	Ballast	Starting Amps/ Operating Amps				Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours
					120V	208V	240V	277V				
	350	ED28	Mogul	CWA HPF QT	3.3/3.6	1.9/2.1	1.7/1.8	1.4/1.6	400	M131	33300	20000

**Factory Installed Options**  
Add suffix to Catalog Number

Swivel Photocontrol (/PCS)  
Single fusing for 120 and 277 volt (/F)  
Double fusing for 208 and 240 volt (/FF)

Button Photocontrol (/PC)  
480 volt ballast (consult factory) (/480)

Note: Specifications may change without notice