



# BLH250AW22DLP



JOB NAME: \_\_\_\_\_

DATE: \_\_\_\_\_

TYPE: \_\_\_\_\_

## DESCRIPTION

Indoor fixtures for use below 25'. 16" units for 250w Metal Halide and HPS. 22" units for 400w Metal Halide and HPS. Die cast aluminum housing, wiring box and semi specular anodized aluminum refractor. ballast and lamp supplied.

## SPECIFICATIONS

### Ballast:

Quad-Tap CWA Ballast (120/208/240/277 Volts)

### Housing:

Die cast aluminum painted white. 3' cord and hook/loop. Heavy-duty sheet metal wiring box with 1/2 knockouts and easy leveling adjustment.

### Junction Box:

Heavy duty stamped steel junction box.

### Patterns:

Field adjustable light distribution patterns

### Plate:

Die-cast plate tapped 3/4" NPS accepts 3/4" pipe or 715NEW die cast hook

### Reflector:

Seven distribution patterns for precise control with seven position adjustable bracket. Spun semi-specular anodized aluminum

### Restrike Time:

10 - 20 minutes

### Socket:

4KV pulse rated mogul base socket

### Start Up Time:

3 - 5 minutes

### UL Listing:

Suitable for damp locations. UL and cUL listed for 40°C (104°F) ambient temperature

### Wiring Compartment:

Removable steel wiring compartment door for quick and easy mounting

### 2005 NEC Compliance:

Open rated lamp and socket comply with 2005 NEC code

### Lamp:

Mogul Base, ED18

### Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

### Pulse Start:

Pulse Start metal halide for increased lamp life, lumen maintenance, color uniformity and efficiency

### Color:

White

### Weight:

24.28

## DIMENSIONS



## ORDERING INFORMATION

Metal Halide Lamp supplied with fixture	Total Watts	Lamp Type	Lamp Base	Ballast	Starting Amps/ Operating Amps				Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours
					120V	208V	240V	277V				
	250	ED28	Mogul Base Up	CWA-HPF QT	1.4/2.5	.8/1.5	.7/1.3	.6/1.1	295	M153/0	23800	15000

### Factory Installed Options

Add suffix to Catalog Number

Note: Specifications may change without notice

**RAB Lighting, Inc.** • 170 Ludlow Ave • Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • [www.rabweb.com](http://www.rabweb.com)  
© 2011 RAB Lighting, Inc.