



BLH400P22DLPSQ

JOB NAME: _____

DATE: _____

TYPE: _____

DESCRIPTION

Indoor fixtures for use below 25'. 16" units for 250w Metal Halide. 22" units for 400w Metal Halide. Die cast aluminum housing and wiring box. Clear acrylic Lexalite Reflexor prismatic refractor. Ballast and lamp supplied.

SPECIFICATIONS

Ballast:

Quad-Tap CWA Ballast (120/208/240/277 Volts)

Housing:

Die cast aluminum painted white. 3' cord and hook/loop. Heavy-duty sheet metal wiring box with 1/2 knockouts and easy leveling adjustment.

Junction Box:

Heavy duty stamped steel junction box.

Patterns:

Field adjustable light distribution patterns

Plate:

Die-cast plate tapped 3/4" NPS accepts 3/4" pipe or 715NEW die cast hook

Reflector:

Reflector with five distribution patterns for precise control

Restrike Time:

10 - 20 minutes

Socket:

4KV pulse rated mogul base socket

Start Up Time:

3 - 5 minutes

UL Listing:

Suitable for damp locations. UL and cUL listed for 40°C (104°F) ambient temperature

Wiring Compartment:

Removable steel wiring compartment door for quick and easy mounting

2005 NEC Compliance:

Open rated lamp and socket comply with 2005 NEC code

Bracket:

Multi-position adjustable reflector bracket

Lamp:

Mogul Base, ED18

Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

Pulse Start:

Pulse Start metal halide for increased lamp life, lumen maintenance, color uniformity and efficiency

Refractor:

Seven distribution patterns for precise control with seven position adjustable bracket. Clear acrylic Lexalite Reflexor® prismatic refractor for long-term resistance to yellowing

Color:

Prismatic

Weight:

30.66

ORDERING INFORMATION

Metal Halide Lamp supplied with fixture	Total Watts	Lamp Type	Lamp Base	Ballast	Starting Amps/ Operating Amps				Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours
					120V	208V	240V	277V				
	400	ED37	Mogul Base Up	CWA-HPF QT	3.5/4.0	2.0/2.3	1.8/2.0	1.5/1.8	458	M155/0	41000	20000
Factory Installed Options Add suffix to Catalog Number												

Note: Specifications may change without notice

RAB Lighting, Inc. • 170 Ludlow Ave • Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • www.rabweb.com
© 2011 RAB Lighting, Inc.