

LANDSCAPE LAWN LIGHTS

Classic Landscape Lawn Lights
packed with rugged features.



Rugged die cast aluminum housing
with durable powder coating.

Socket with all copper electrical parts and 20" leads

Quick and secure installation with one
corrosionproof screw

Threaded, gasketed globes for durable
weatherproofing and easy relamping

12" color matched mounting stem
with 1/2" threads available

Includes easy mounting 1/2" threaded nipple



For sturdy Lawn Light mounting,
use RAB Mighty Posts
(see pages 96-97)



Barbara explains the benefits
of Mighty Post.



Rugged path lights with louvers to direct light
downward blend with any landscaping.

Product Information

Incandescent (120 volt)
Lamp not supplied

Compact Fluorescent (120 volt)
Lamp supplied with fixture.
Minimum operating temperature 32°
NPF 120 volt ballast

Lamp Watts	Lamp Type	Lamp Base	Initial Lumens	Lamp Hours
75	A-19	Med	1220	750
100	A-19	Med	1650	750
13	Quad	GX23-2	860	10,000

Specifications

UL Listing:

Suitable for wet locations. Suitable for mounting within 4 feet of the ground.

Socket:

Medium base porcelain with all copper electrical parts and 20" leads, including a ground lead.

Lamps:

Incandescent- (not supplied)
Medium base A-19 lamps, 120V.
4-tier - 100 watt max.
3-tier - 75 watt max.
Fluorescent- (supplied)
13 watt quad tube
NPF 120v ballast

Globes:

Threaded, gasketed globe protects against weather, garden sprinklers and insects. Clear glass GL100 globes standard for 4 Tier. Clear glass GL60 globes standard for 3 Tier. GL100 white globes also available for attractive appearance and glare reduction.

Housing:

Die cast aluminum housing with powder coat finish.

Voltage:

120 volts AC

Replacement Parts:

Part	Catalog #
Socket	SLL
Globe for 4 tier -clear	GL100
Globe for 4 tier -white	GL100W
Globe for 3 tier - clear	GL60
Globe for 3 tier - white	GL60W

Mounting Stem:

Accessory 12" mounting stem with 1/2" threads on both ends available

Part	Catalog #
12" Stem Verde Green	ST12VG
12" Stem Black	ST12B

Mighty Post Mounting:

See page 96.

Fax Info on Demand 24/7

Call RAB FaxBack at 888 722-1236.

Enter document numbers shown below:

	Catalog Page	Installation Manual
LL22	270	276
LL23	270	276
LL322	270	278
LL323	270	278

For more info on RAB FaxBack see p.170

Product Info on the Internet:

www.rabweb.com, click "support"

Four Tier 6"

Rugged die cast aluminum 6" diameter housings. Threaded, gasketed clear glass globe for durable weatherproofing and easy relamping. 1" long, 1/2" threaded nipple included for easy mounting. 100 watt max. Lamp not included.

Finish: ● Black
● Verde Green



Four Tier Flare

10" diameter top tier, 6" diameter lower tier. Rugged die cast aluminum housings. Threaded, gasketed clear glass globe for durable weatherproofing and easy relamping. 1" long, 1/2" threaded nipple included for easy mounting. 100 watt max. Lamp not included.

Finish: ● Black
● Verde Green



Three Tier 6"

Rugged die cast aluminum 6" diameter housings. Threaded, gasketed clear glass globe for durable weatherproofing and easy relamping. 1" long, 1/2" threaded nipple included for easy mounting. 75 watt max. Lamp not included.

Finish: ● Black
● Verde Green



Three Tier Flare

10" diameter top tier, 6" diameter lower tiers. Rugged die cast aluminum housings. Threaded, gasketed clear glass globe for durable weatherproofing and easy relamping. 1" long, 1/2" threaded nipple included for easy mounting. 75 watt max. Lamp not included.

Finish: ● Black
● Verde Green



Catalog Numbers

Verde Green	Black
LL22VG	LL22B
LL22VG/F13	LL22B/F13

Verde Green	Black
LL23VG	LL23B
LL23VG/F13	LL23B/F13

Verde Green	Black
LL322VG	LL322B
LL322VG/F13	LL322B/F13

Verde Green	Black
LL323VG	LL323B
LL323VG/F13	LL323B/F13

Dimensions

