

EZ Grip locknut matches fixture finish and can be adjusted with fingers, pliers or a screwdriver



Unique panning pivot keeps lamp level for extended life

Specifications 🖤

UL Listing: Suitable for wet locations.

Housing:

Precision die cast aluminum. 1/2" NPS threaded arm with three locking incandescent swivels. Fits all standard mounting covers.

Lens Gasket:

High temperature silicone gasket stays in place during relamping.

Reflector: Semi-specular anodized aluminum

Socket: Porcelain RSC base sockets with spring loaded center contacts.

Lens:

Tempered shock resistant glass



Finish: Chip and fade resistant durable powder coat finish.

Replacement Lamps:

	at the last
Fixture	Lamp
	Cat #
Q1	LQ150

<u>Cat #</u>	
LQ150	
LQ300	

Patents:

03


The designs of RAB fixtures are protected under U.S. and international intellectual property laws.

Info Online 24/7

Spec Sheets, Installation Manuals, Wiring Diagrams & Photometrics www.rabweb.com > click "PRODUCTS"

Photometrics

300w Fixture @ 15' Mounting Height Aimed 30° below horizontal





Catalog Numbers

Bronze	White	Bronze	White
Q1A	Q1W	Q3A	Q3W

Dimensions

