

# VAPORPROOF ENTRY LIGHTS

**New!** Brighten entranceways with durable, economical ceiling and wall bracket fixtures in classic shapes.



*Dusk to Dawn Photocell models available*

*Die cast aluminum for superior durability*

*Decorative white heat resistant glass or polycarbonate globes available*

*High temperature silicone internal gaskets*

*Premium porcelain socket*

*UL Listed for use with 90°C supply wiring  
OK for use in dwellings and wet locations*



## Product Information

**Compact Fluorescent**   
Lamp supplied with fixture

Watts	Lamp Type	Lamp Base	Ballast
13	13w Quad	GX23-2	NPF 120V
13	13w Quad	GX23-2	NPF 120V
13	13w Quad	GX23-2	NPF 120V
13	13w Quad	GX23-2	NPF 120V
26	2-13w Twin	GX23	NPF 120V
26	2-13w Twin	GX23	NPF 120V

**High Pressure Sodium**  
Lamp supplied with fixture

Watts	Lamp Type	Lamp Base	Ballast
50	ED17	Medium	R-NPF 120V
50	ED17	Medium	R-NPF 120V

**Incandescent**  
Lamp not supplied

Watts	Lamp Type	Lamp Base	Ballast
75	A19	Medium	
75	A19	Medium	

Starting Amps 120V	Operating Temp	Input Watts	Lamp ANSI	Initial Lumens	Lamp Hours	
.4	32°			825	10,000	<b>Glass Globe</b>
.4	32°			825	10,000	<b>Glass Globe w/ Photocell</b>
.4	32°			825	10,000	<b>Polycarbonate Globe</b>
.4	32°			825	10,000	<b>PC Globe w/ Photocell</b>
.4	0°			1625	10,000	<b>Polycarbonate Globe</b>
.4	0°			1625	10,000	<b>PC Globe w/ Photocell</b>
1.5 / 1.2		62	S68	4,000	24,000	<b>Glass Globe</b>
1.5 / 1.2		62	S68	4,000	24,000	<b>Polycarbonate Globe</b>
				1,210	1,500	<b>Glass Globe</b>
				1,210	1,500	<b>Polycarbonate Globe</b>

## Specifications

**UL Listing:**  
Suitable for wet locations.  
Suitable for use in dwellings.  
Suitable for use with 90°C supply wiring.  
Complies with UL Standard 1598.

**Finish:**  
Chip and fade resistant architectural bronze or bright white polyester finish.

**Housing:**  
Die cast aluminum.

**Globes:**  
White glass or unbreakable polycarbonate white globes.  
For replacement globes see pages 154-155



**Socket:**  
HID: Glazed porcelain 4kv pulse rated with nickel plated screw shell and spring contacts.  
CFL: White thermo plastic with integral clips for lamp retention.

**Patents:**  
The designs of RAB fixtures are protected under U.S. and international intellectual property laws.

**Spec Sheets, Installation Manuals, Wiring Diagrams & Photometrics 24/7**  
[www.rabweb.com](http://www.rabweb.com) > click "PRODUCTS"

**New!**

### Ball Entry

Entry light in 13 watt compact fluorescent, 50 watt HPS and 75 watt max. incandescent. Cast aluminum housing with decorative white glass globe or unbreakable polycarbonate. Bracket fixture mounts to common junction boxes. Photocell models available. CFL and HPS lamps supplied. Incandescent lamp not supplied.

Finish: ● Bronze  
○ White



**New!**

### Plastic Cylinder Entry

Entry light in 13w and 26w compact fluorescent, 50 watt HPS and 75 watt max. incandescent. Cast aluminum housing with unbreakable white polycarbonate globe. Bracket fixture mounts to common junction boxes. Photocell models available. CFL and HPS lamp supplied. Incandescent lamp not supplied.

Finish: ● Bronze  
○ White



**New!**

### Ceiling Entry Light

Ceiling fixture for 13 watt compact fluorescent or incandescent lamps. Satin aluminum with cylinder shaped white glass (100 watt max.) or unbreakable polycarbonate white globe (75 watt max.) CFL lamp supplied. Incandescent lamp not supplied.

Finish: ● Satin Aluminum



## Catalog Numbers

Bronze	White
VBF13BA	VBF13BW
VBF13BA/PC	VBF13BW/PC
VBF13BPA	VBF13BPW
VBF13BPA/PC	VBF13BPW/PC
VBS50BA	VBS50BW
VBS50BPA	VBS50BPW
VB75BA	VB75BW
VB75BPA	VB75BPW

Bronze	White
VBF13CPA	VBF13CPW
VBF13CPA/PC	VBF13CPW/PC
VBF26CPA	VBF26CPW
VBF26CPA/PC	VBF26CPW/PC
VBS50CPA	VBS50CPW
VB75CPA	VB75CPW

Satin Aluminum	
VCF13CSA	
VCF13CPSA	
VCF13CSA	
VCF13CPSA	

## Dimensions

