



Architectural Landscape Floods

ORDERING INFORMATION


920	
75W max. Wattage - Open Bullet	
920	Gray finish
920P	Bronze finish
920B	Black finish
920G	Green finish
920W	White finish



PRODUCT SPECIFICATIONS

- Architectural Bullets are designed for safety, security, and accent lighting. Areas requiring good color rendition, instant-on, dimming capability, easy installation and low initial cost.
- Precision die-cast aluminum finished in polyester powder in a variety of colors.
- Premium porcelain socket with plated medium base screw shell and reinforced center contact for positive fit.
- 1/2" NPT threaded adjustable arm, locknut preinstalled, prelubed to facilitate mounting.
- Cast-in quadrants with serrated teeth lock unit in place once aimed.
- Extra long pigtailed for easy splicing.
- Units equipped with weep holes for open fixture applications.
- Open units.
- UL listed for above horizontal aiming with PAR lamps. Enclosed units UL listed for above horizontal aiming with R or PAR lamps.

3800	
300W max. Wattage	
3800	Gray finish
3800P	Bronze finish
3800B	Black finish
3800G	Green finish
3800W	White finish



ACCESSORIES

For Enclosed 920 and 3800 Series

	920 Extender	920 Shield	3800 Extender	Concave Glass
Gray	9250E	9255E	3850E	3851E
Bronze	9250EP	9255EP	3850EP	3851EP
Black	9250EB	9255EB	3850EB	3851EB
Green	9250EG	9255EG	3850EG	3851EG
White	9250EW	9255EW	3850EW	3851EW

TECHNICAL INFORMATION

Architectural Bullet Series are not supplied with lamp. Open 920 Series accepts PAR20. Enclosed accepts PAR20 or R20 lamps. Open 3800 Series accepts PAR38. Enclosed accepts PAR38 or R40 lamps. Beam spread determined by lamp type.

See page 6-A for Lamp Data.



UL Wet Location Listed.
UL File Number: E57163