

MINI-BLOWERS



24" & 30" FLOOR MODEL



24" & 30" YOKE MOUNTED MODEL
AND
OPTIONAL WALL/CEILING MOUNT

TOTALLY ENCLOSED MOTOR ALLOWS MINI-BLOWER TO BE USED
IN DIRTY OR DUSTY ENVIRONMENTS.

AVAILABLE AS FLOOR MODEL OR YOKE MOUNTED MODEL THAT
CAN BE DIRECTLY BOLTED TO ANY SURFACE OR USED WITH
OPTIONAL WALL/CEILING MOUNT.

SIZE 24" & 30"

MOTOR 2-speed, 1/4 HP, 1 Phase, 120 volt,
ball bearing, permanently lubricated,
totally enclosed, permanent split
capacitor.

SWITCH Rotary on floor models
Pull chain on yoke mounted model

CORD SJT type - 3 conductor - 10' long

BLADE Aluminum

GUARDS Spiral wire - front and rear

HOUSING . . . Powder coated 20 ga. steel

- Meets OSHA Standards
- 1 Year Limited Warranty



UPC CODE 686334	MODEL NUMBER	FAN TYPE	SIZE	CFM		AMPS	SHIPPING WT.(LBS.)	LIST PRICE
				HIGH	LOW			
798457	MB 24-DF	FLOOR STYLE	24"	6800	5000	2.2	52	513
798464	MB 24-DY	YOKE STYLE					52	513
798853	MB 30-DF	FLOOR STYLE	30"	7800	6000	2.5	58	567
798860	MB 30-DY	YOKE STYLE					58	567
798907	MBM-W	OPTIONAL WALL/CEILING MOUNT FOR YOKE STYLE MINI-BLOWER					4	103