


Stellos Low Voltage Halogen

3388

Downlight



LUMINAIRE INFORMATION

APPLICATION:

Accent luminaire for Residential, Commercial, Retail or Hospitality environments.

MATERIALS:

Trim: Die cast aluminum. Torsion spring mounting.
Lens: Clear.

LAMP: (not included) When using IR lamps, 37W Max.
(1) 75W Max. MR16 GU5.3.

TRANSFORMER:

Magnetic toroidal-HPF. Low voltage solid state electronic optionally available (consult factory).
Note: Due to transformer / dimmer match some dimmers may cause transformer hum. Check with dimmer manufacturer for suitability.

VOLTAGE:

Specify 120V or 277V.

CEILING CUT OUT:

4 3/8" Ø

LISTINGS:

Dry/damp/wet under cover ceiling.



IC/Airtight housing meets Washington state airflow requirement and ASTM E283.


Chicago Plenum housing is Chicago Plenum rated.

IBEW union made.

NOTES:

- Maximum ceiling thickness 1 inch. Consult factory for other ceiling conditions.
- Maximum 2 lens options (size B).

PHOTOMETRICS:



Bare lamp photometrics
75W MR16 GU5.3 36°

Ft below	FC nadir	Dia. @ 50%
6.0	70.2	5.2
8.0	39.5	6.2
10.0	25.2	7.3
12.0	17.5	8.3
14.0	12.9	9.4
16.0	9.8	10.4

HOUSING INFORMATION

New Construction
50TW - (50W)













New Construction
75TW - (75W)

IC/Airtight
50ICN - (50W)

Chicago Plenum
50TWCP - (50W)

Remote Transformer
50RM - (50W)

Retrofit
100 - (50W)



14 3/4"

15 1/2"

17 5/8"

15 1/2"

14 3/4"

13 7/8"

ORDERING INFORMATION

Trim

3388 - Shallow Regress
Stellos
Downlight,
75W Max. MR16 GU5.3

- Finish

10 - White
21 - Black
28 - Metalized Grey

- Housing

50TW - New Construction
75TW - New Construction
50ICN - IC/Airtight
50TWCP - Chicago Plenum
50RM - Remote Transformer
100 - Retrofit

- Voltage

120V
277V

- Accessories

8177B - Hex Cell Louver
9143B - Frosted Lens
9153B - Anti UV Filter
9155B - Linear Spread Lens
9156B - Prismatic Spread Lens
9157B - Solite Lens
9199B - Frosted Borosilicate Lens
ER - Emergency Relay

How to Specify

3388 - _____ - _____ - _____ - _____
Trim - Finish - Housing - Voltage - Accessories



USA Illumination™
www.usaillumination.com
info@usaillumination.com

1126 River Road
New Windsor, NY 12553

T 845-565-8500
F 845-561-1130

© 2009, USAI, LLC.
All rights reserved.
All designs protected by copyright.
09/02/2010