

100 square plaster-in floor wash

A 4 inch low level floor wash luminaire with flush trim for absolute minimal visual impact. Open aperture with asymmetric scoop reflector.

Applications:

- Trimless, plaster-in for drywall.
- Installation from room side of the wall for remodel or new construction.

Features:

- 'Easy click' tool free installation and maintenance of lamp module.
- Heavy gauge steel housing with integral plaster-in flange
- Pre-wired with a 'Plug and Play' electrical connection for remote mounted Class 2 driver. Secondary Class 2 power cable supplied by others (quick connector on fixture supplied.)
- Powdercoat painted white - RAL 9010.

project specification

P100SFW								
series	-	lamp type	-	wattage	-	voltage	-	options

ordering information

series	lamp type	wattage	voltage	options	cut-out dimensions
P100SFW plaster-in 4" square floor wash	- LEDBR - 830 420 lm, 3000K (f)	- 8 (LEDBR)	- 120V (b,e) - 277V (a,b,c,d)	- DIM010 (a) - DIMELV (b) - DIML3D (c) - DIMLTE (d)	4 5/8" x 4 5/8"

Notes:

- Remote mounted 120/277V dimmable driver (0-10V)
Driver(s) ordered separately. Operates 3-4 fixtures
- Remote mounted 120V dimmable driver (Electronic Low Voltage)
Driver(s) ordered separately. Operates 1-4 fixtures
- Remote mounted 120/277V dimmable driver (Lutron A-Series, 3D)
Driver(s) ordered separately. Three wire and EcoSystem compatible.
Operates 1-2 fixtures. Contact factory for other fixture quantities.
- Remote mounted 120/277V dimmable driver (Lutron A-Series, TE)
Driver(s) ordered separately. Forward phase with neutral required.
Operates 1-2 fixtures. Contact factory for other fixture quantities.
- Remote mounted 120V non-dimmable driver (Electronic Low Voltage)
Driver(s) ordered separately. Operates 1 fixture.
- Specify 840 (4000K), 80 CRI.

